




















Handling System

From the most sophisticated antropomorphic robots in the warehouses of the great distribution giants, to the basic house hardware, handling equipments are helping nowadays to creat efficiency and cost effective operations. These handling systems have contributed to make factories more productive and efficient too.

Vitap is glad to present a new department dedicated to automation which is interconnected to the fleet of compact CNC working centers of K2 2.0 and Acoustic series, allowing the creation of productive cells. Vitap philosophy aims to evolve, together her customers, from stand alone working centers to a self feeding and stacking working cell thanks to a tailored automation system.



The new **FLOW** handling system has been thought for high and flexible productions. Specially designed to load and unload throughfeed longitudinal working centers. The advantage of a compact (also as an investment) handling system like **FLOW** is the capacity to constantly feed the machine without any operator except for feeding and taking out the stacks to be worked and the already worked stacks. One operator can easily manage 2 or 3 **FLOW** systems with a large production output yet very flexible.





EFLOW 25


Automation K2 2.0














PANEL DIMENSIONS

min length = 400

Max length = 1.500

min width = 300

Max width = 1.200

EFLOW 45

Automation K2 2.0










Example 2 top of a base unit with minifix

Pieces per minute	2 pcs
Pieces per stack circa	70 pcs
Stacks	4
Working time including lunch tin	ne and
1 extra hour without operator	10 hours
In minutes	600 minutes
Total out put	1.200 pcs







PANEL DIMENSIONS


min length =	400
Max length = '	1.500
min width =	300


EFLOW 45


Automation K2 2.0












PANEL DIMENSIONS

min length = 400Max length = 1.500min width = 300

Max width = 700


BATCH SIZE 1





Automation K2 2.0
















PANEL DIMENSIONS


min length = 400 Max length = **2.400** min width = Max width = 700


EFLOW #Acoustic



Automation Acoustic







PANEL DIMENSIONS

min length = 400

Max length = 2.400

min width = 300

Max width = 700


* depending to the dimension of the panel

Automation K2 2.0

600 minutes

840 pcs











Example 6 piece with big hole in center Pieces per minute **1,4** pcs Pieces per stack circa **70** pcs Stacks 2 pcs Working time including lunch time and 1 extra hour without operator 10 hours

In minutes

Total out put







PANEL DIMENSIONS

min length = 400 Max length = **1.500** min width = 300Max width = 1.200

Automation K2 2.0


⊞K2 2.0







Automation K2 2.0

⊞K2 2.0






EFLOV 4L




Automation K2 2.0









PANEL DIMENSIONS

min length = 400

Max length = 2.400

min width = 300

Max width = 700