

MAGPRINT CUSTOM WALLS

Product	MagPrint Wall Art and MagPrint Wall Maps
Description	<p>MagPrint Custom Walls are made using MagPrint for low receptive magnet use + MagLiner for high receptive magnet use</p> <p>1. Optional Extra: MagLiner has a grey brown surface:</p> <ul style="list-style-type: none">- high receptive ferrous liner that is used to boost receptivity- easy to hang with ready-mixed wallpaper paste- grey brown surface- supplied boxed in 61cm x 5, 6, 10 or 12m rolls <p>2. MagPrint has a white soft sheen printable surface:</p> <ul style="list-style-type: none">- has low receptive ferrous vinyl that can be digitally printed- easy to hang with ready-mixed wallpaper paste- high white silk vinyl surface- supplied printed and trimmed to make equal width drops up to 111cm wide
Receptivity Rating	MagPrint Soft Sheen: 3/5 MagLiner Grey Brown: 5/5
Weight	MagPrint - 475 grammes per square metre MagLiner - 1800 grammes per square metre
Fire Rating	EuroClass EN13501-1
Roll Dimensions	MagPrint Soft Sheen: 111cm width x 25m lengths (max) MagLiner Grey Brown: 61cm x 5m, 6m, 10m and 12m lengths
Adhesive	MAGFIX Adhesive or any high quality ready-mixed wallpaper paste
Warranty	7 Years
Maintenance:	- clean using a damp cloth and micro fibre cloth
Magnet Usage:	- MagPrint works with low power magnets - MagLiner works with both low and high power magnets - MagPlus are high power neodymium magnets for holding items to the wall - MagLite are low power sheet magnets for decorative placement use
Health and Safety:	Warning - high power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
Classification:	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting:	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.



INSTALLATION GUIDE

Configuration

It is recommended that MagPrint Custom Wallcoverings are hung vertically. Other configurations are possible as shown above.

Tools:

- A felt or sponge roller for paste application
- Scissors or sharp blade knife
- Straight edge
- Soft wallpaper brush
- Microfibre cloth or sponge

Wall preparation:

- MagPrint Custom Wallcoverings work best when applied to mirror smooth plaster surface
- ensure the wall surface is clean, dry, sound, mirror smooth and free from paint or chemicals
- best results will be obtained if the base plaster is sealed with a PVA sealer
- where necessary fill holes with filler and use fine sandpaper to smooth

Hanging guide:

- for best writing experience it is recommended that MagPrint is applied vertically
- allow wallcoverings to adjust to room temperature
- custom wallcoverings are supplied cut into required widths and lengths
- ensure wallcoverings are hung using MagFix or any high quality ready-mixed adhesive
- pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops (allow 5-7 mins for adhesive to become tacky)
- apply the cut lengths, edge to edge, vertically working from left to right
- apply MagLiner to the wall (shiny side to face the wall)
- apply MagPrint to the wall (non print side to face the wall)
- use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
- ensure images align on joins
- use a straight edge and sharp trimming knife at corners and edges
- do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
- remove any excess paste with a damp sponge and wipe surface clean
- leave to dry thoroughly (min 24 hrs)

Finishing options:

MagLiner:

- to use high power magnets, ensure that you first apply MagLiner to the wall. Allow to dry (min 24hrs) before applying the MagPrint Custom Wallcovering on top.

Removal:

- gently strip wallcoverings away from wall using a scraper
- MagLiner will retain its receptive quality so may be re-used if undamaged

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.