

## MagChalk: USER GUIDE

<b>Product</b>	<b>MagChalk - magnetic wallpaper, high receptivity</b>
<b>Description</b>	<p><b>MagChalk has a high receptivity rating so works with both MagPlus and MagLite magnet types.</b></p> <p><b>MagChalk Matt has a non-reflective matt dry-erase surface with features that include:</b></p> <ul style="list-style-type: none"> <li>- hard wearing matt surface for chalks or chalk pens</li> <li>- Clean using generic whiteboard spray and microfibre cloth.</li> <li>- easy to hang in multiple configurations</li> <li>- available at 120cm width by 3m and 6m lengths</li> </ul>
<b>Receptivity Rating</b>	4/5
<b>Weight</b>	1800 grammes per square metre
<b>Fire Rating</b>	EuroClass D-s1, d0
<b>Roll Dimensions</b>	MagChalk Matt: 120cm width x 3m and 6m lengths
<b>Adhesives</b>	MagVOV Adhesive
<b>Warranty</b>	7 Years
<b>Maintenance:</b>	<ul style="list-style-type: none"> <li>- MagChalk works with all high-quality chalks and chalk pens</li> <li>- Clean with Whiteboard Spray and Microfibre Cloth</li> <li>- Regularly clean surface to keep in optimum condition</li> <li>- Important: Avoid abrasive cleaners and cheap pens as they can scratch the surface</li> </ul>
<b>Magnet Usage:</b>	<ul style="list-style-type: none"> <li>- MagChalk has high receptivity so works with all magnet types</li> <li>- MagPlus are high-power neodymium magnets for holding items</li> <li>- MagLite are low-power sheet magnets for placement use</li> </ul>
<b>Health and Safety:</b>	Warning - high-power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
<b>Classification:</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Fire Fighting:</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological:</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.



## MagChalk: DECORATOR GUIDE

### Configuration

It is recommended that MagChalk Wallcoverings are hung horizontally and positioned at optimum writing height for comfortable writing experience. Other configurations are possible as shown above.

### Tools:

- A felt or sponge roller for paste application
- Scissors or sharp blade knife
- Straight edge
- Soft wallpaper brush
- Microfibre cloth or sponge
- Clean water and mild detergent

### Wall preparation:

- MagChalk writing materials work best when applied to mirror smooth plaster surface
- ensure the wall surface is clean, dry, sound, mirror smooth and free from paint or chemicals
- best results will be obtained if the base plaster is sized with adhesive or sealed with a PVA
- where necessary fill holes with filler and use fine sandpaper to smooth

### Adhesives/Primers:

#### - for plaster boards/walls:

- prepare base wall with a PVA (Unibond Super PVA) to create a seal.
- apply MagVOV Adhesive directly to the wall and apply pre-cut strips of MagChalk.

#### - for mdf/plywood/panels:

- prepare base panel with an oil based primer to create a seal (Zinsser 'All Coat' Solvent Base Primer).
- apply MagVOV Adhesive directly to the panel and apply pre-cut strips of MagChalk.

Note: We strongly advise that you test in advance before any major installation.

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

## MagScapes Limited

5 Albemarle Way  
Clerkenwell  
London  
EC1V 4JB  
T: +44 (0) 800 804 4936  
W: [www.magscapes.com](http://www.magscapes.com)

### Hanging guide:

- for best writing experience it is recommended that MagChalk is applied horizontally
- allow wallcoverings to adjust to room temperature
- cut wallcovering into required lengths
- ensure wallcoverings are hung using the recommended adhesive/primer option (see above)
- pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops
- apply the cut lengths, edge to edge, vertically or horizontally as required
- apply MagChalk to the wall (grey marbled side to face the wall)
- use a microfibre cloth covered straight edge to flush out air bubbles across all areas of the surface using sweeping action from the centre outward
- use masking tape to top edge to secure if likely to slip during install
- use a straight edge and new blade knife to trim corners and edges
- do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
- immediately remove any excess paste with a damp sponge with mild detergent and wipe surface clean
- leave to dry thoroughly (min 24 hrs)

### Finishing options:

#### Seams:

- MagChalk is machine cut for butt joined seams. Try to have seams placed where the chalks are least likely to cross to reduce visible build-up on seams.

#### Edging:

- to prevent chalks from skipping on to non-writeable areas it is recommended that a decorative edging strip is used

#### Removal:

- to remove, gently strip away from wall using a scraper

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl - do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.