



## MagLiner: USER GUIDE

<b>Product</b>	<b>MagLiner - magnetic wallpaper, high receptivity</b>
<b>Description</b>	<p><b>MagLiner has a high receptivity rating so works with both MagPlus and MagLite magnet types. MagLiner is an easy to hang matt grey versatile liner with finishing options that include:</b></p> <ul style="list-style-type: none"> <li>- finish option a: use raw using the grey matt finish</li> <li>- finish option b: use under a wallpaper, digital print or fabric</li> <li>- finish option c: use under dry-erase or chalk adhesive laminate</li> <li>- finish option d: use with all-purpose primer for any paint finish</li> </ul>
<b>Receptivity Rating</b>	5/5
<b>Weight</b>	1800 grammes per square metre
<b>Fire Rating</b>	Not Applicable
<b>Roll Dimensions</b>	61cm width x 5m, 6m, 10m, 12m lengths
<b>Adhesives/Primers</b>	MagFix Adhesive / PVA Primer, Tekfix VOV / Zinsser 'AllCoat' Solvent Base Primer
<b>Warranty</b>	7 Years
<b>Maintenance:</b>	- clean using a damp micro fibre cloth
<b>Magnet Usage:</b>	<ul style="list-style-type: none"> <li>- MagLiner has high receptivity so works with all magnet types</li> <li>- MagPlus are high power neodymium magnets for holding items</li> <li>- MagLite are low power sheet magnets for placement use</li> </ul>
<b>Health and Safety:</b>	Warning - high power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
<b>Classification:</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Fire Fighting:</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological:</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

## MagLiner: DECORATOR GUIDE

### Configuration

MagLiner Wallcoverings may be hung in any of the configurations shown above.

### Tools:

- A felt or sponge roller for paste application
- Scissors or sharp blade knife
- Straight edge
- Soft wallpaper brush
- Microfibre cloth or sponge

### Wall preparation:

- ensure the plaster wall surface is clean, dry, sound, mirror smooth and free of paint or chemicals
- best results will be obtained if the base plaster is sealed with a PVA sealer
- where necessary fill holes with filler and use fine sandpaper to smooth

### Adhesives/Primers:

#### - for plaster boards/walls:

- prepare base wall with a PVA (Unibond Super PVA) to create a seal.
- apply a high-quality, ready-mixed adhesive (MagFix) or (Wallrock Power Adhesive) directly to the wall and apply pre-cut strips of wallcovering.

#### - for mdf/plywood/panels:

- prepare base panel with an oil based primer to create a seal (Zinsser 'AllCoat' Solvent Base Primer).
- apply a Tekfix VOV adhesive directly to the wall and apply pre-cut strips of wallcovering.

Note: We strongly advise that you test in advance before any major installation.

### Hanging guide:

- allow wallcoverings to adjust to room temperature
- cut wallcovering into required lengths
- ensure wallcoverings are hung using the recommended adhesive/primer option (see above)
- pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops
- apply the cut lengths, edge to edge, vertically or horizontally as required
- apply MagLiner to the wall (shiny side to face the wall)
- use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
- use masking tape to secure if likely to slip during install
- use a straight edge and sharp trimming knife at corners
- do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
- remove any excess paste with a damp sponge and wipe surface clean
- leave to dry thoroughly (min 24 hrs)

## **MagScapes Limited**

5 Albemarle Way  
Clerkenwell  
London  
EC1V 4JB  
T: +44 (0) 800 804 4936  
W: [www.magscapes.com](http://www.magscapes.com)

### **Finishing options:**

#### **Wallcovering:**

- hang wallcovering or digital print on top following recommended guide

#### **Laminates:**

- for dry erase or chalk laminate, carefully peel one corner back and apply to the wall in the correct position  
- slowly peel backing sheet away as you apply the material, flushing air bubbles and creases as you go

#### **Paint:**

- apply all-purpose primer (Zinsser) allow to dry and then overpaint with any emulsion

#### **Removal:**

- gently strip away from wall using a scraper  
- MagLiner will retain its receptive quality so may be re-used if undamaged on removal

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.