



MagLiner: USER GUIDE

Product	MagLiner - magnetic wallpaper, high receptivity
Description	<p>MagLiner has a high receptivity rating so works with both MagPlus and MagLite magnet types. MagLiner is an easy to hang matt grey versatile liner with finishing options that include:</p> <ul style="list-style-type: none"> - finish option a: use raw using the grey matt finish - finish option b: use under a wallpaper, digital print or fabric - finish option c: use under dry-erase or chalk adhesive laminate - finish option d: use with all-purpose primer for any paint finish
Receptivity Rating	5/5
Weight	1800 grammes per square metre
Fire Rating	Not Applicable
Roll Dimensions	61cm width x 5m, 6m, 10m, 12m lengths
Adhesives/Primers	MagFix Adhesive / PVA Primer; Zinsser 'AllCoat' Solvent Base Primer
Warranty	7 Years
Maintenance:	- clean using a damp micro-fibre cloth
Magnet Usage:	<ul style="list-style-type: none"> - MagLiner has high receptivity so works with all magnet types - MagPlus are high power neodymium magnets for holding items - MagLite are low power sheet magnets for placement use
Health and Safety:	Warning - high power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
Classification:	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting:	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological:	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

MagScapes: DECORATOR GUIDE

MagScapes Wallcoverings are created to be hung with paste in any of the configurations shown above.

- Tools:**
- Roller and tray for paste application
 - Scissors and sharp blade knife
 - Straight edge
 - Soft wallpaper brush
 - Flexible wallpaper smoother
 - Micro-fibre cloth or sponge

- Wall preparation:**
- ensure the plaster wall surface is clean, dry, sound and free of flaky paint or chemicals
 - de-nib the wall with a wide scraper
 - where necessary fill holes with filler and use fine sandpaper to leave smooth (see smoothness guide below)
 - for plaster/board walls - best results will be obtained if the wall is 'sized' with a diluted adhesive or PVA seal
 - for mdf/plywood/panels - prepare panels with an all-purpose primer to create a seal (Zinsser Bulls Eye 1-2-3 Stain Killer Primer Sealer).

* Smoothness Guide:

- | | |
|----------------|---------------------|
| MagLiner | - reasonably smooth |
| MagPaintable | - smooth |
| MagPrint | - very smooth |
| MagWrite Matt | - very smooth |
| MagWrite Gloss | - mirror smooth |

- Adhesives/Primers:**
- for lightweight wallcoverings apply MagFix ready-mixed adhesive to the wall and apply pre-cut strips of wallcovering.
 - for heavyweight wallcoverings apply MagVOV ready-mixed adhesive to the wall and apply pre-cut strips of wallcovering.
 - apply a MagVOV adhesive directly to the wall and apply pre-cut strips of wallcovering.

Note: We strongly advise that you test in advance before any major installation.

- Hanging guide:**
- allow wallcoverings to adjust to room temperature
 - cut wallcovering into required lengths
 - ensure wallcoverings are hung using the recommended adhesive/primer option (see above)
 - pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops
 - apply the cut lengths, edge to edge, vertically or horizontally as required
 - apply MagLiner to the wall (shiny side to face the wall)
 - use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
 - use masking tape to secure if likely to slip during install
 - use a straight edge and sharp trimming knife at corners
 - do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
 - remove any excess paste with a damp sponge and wipe surface clean
 - leave to dry thoroughly (min 24 hrs)

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

MagScapes Limited

5 Albemarle Way
Clerkenwell
London
EC1V 4JB
T: +44 (0) 800 804 4936
W: www.magscapes.com

MagLiner Finishes:

Wallcovering:

- paste any wallcovering or digital print directly on top of MagLiner by following manufacturers guides

Dry Erase: the

- for dry-erase finish apply laminate, carefully peel one corner back and apply to the wall in correct position

- slowly peel backing sheet away as you apply the material, flushing air bubbles and creases as you go

Paint:

- apply all-purpose primer (Zinsser) allow to dry and then overpaint with any emulsion

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.