



## MagLiner: USER GUIDE

<b>Product</b>	<b>MagLiner - magnetic wallpaper, high receptivity</b>
<b>Description</b>	<p><b>MagLiner has a high receptivity rating so works with both MagPlus and MagLite magnet types. MagLiner is an easy to hang matt grey versatile liner with finishing options that include:</b></p> <ul style="list-style-type: none"> <li>- finish option a: use raw using the grey matt finish</li> <li>- finish option b: use under a wallpaper, digital print or fabric</li> <li>- finish option c: use under dry-erase or chalk adhesive laminate</li> <li>- finish option d: use with all-purpose primer for any paint finish</li> </ul>
<b>Receptivity Rating</b>	5/5
<b>Weight</b>	1800 grammes per square metre
<b>Fire Rating</b>	Not Applicable
<b>Roll Dimensions</b>	61 cm width x 6m and 12m lengths
<b>Adhesives/Primers</b>	MagFix Adhesive / PVA Primer; Zinsser 'AllCoat' Solvent Base Primer
<b>Warranty</b>	10 Years
<b>Maintenance:</b>	- clean using a damp micro-fibre cloth
<b>Magnet Usage:</b>	<ul style="list-style-type: none"> <li>- MagLiner has high receptivity so works with all magnet types</li> <li>- MagPlus are high power neodymium magnets for holding items</li> <li>- MagLite are low power sheet magnets for placement use</li> </ul>
<b>Health and Safety:</b>	Warning - high power magnets can be dangerous if ingested and should not be used by young children, always read safety information provided.
<b>Classification:</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Fire Fighting:</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological:</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

## MagScapes: DECORATOR GUIDE

MagScapes Wallcoverings are created to be hung with paste in any of the configurations shown above.

- Tools:**
- Roller and tray for paste application
  - Scissors and sharp blade knife
  - Straight edge
  - Soft wallpaper brush
  - Flexible wallpaper smoother
  - Micro-fibre cloth or sponge

- Wall preparation:**
- ensure the plaster wall surface is clean, dry, sound and free of flaky paint or chemicals
  - de-nib the wall with a wide scraper
  - where necessary fill holes with filler and use fine sandpaper to leave smooth (see smoothness guide below)
  - for plaster/board walls - best results will be obtained if the wall is 'sized' with a diluted adhesive or PVA seal
  - for mdf/plywood/panels - prepare panels with an all-purpose primer to create a seal (Zinsser Bulls Eye 1-2-3 Stain Killer Primer Sealer).

\* Smoothness Guide:

- |                |                     |
|----------------|---------------------|
| MagLiner       | - reasonably smooth |
| MagPaintable   | - smooth            |
| MagPrint       | - very smooth       |
| MagWrite Matt  | - very smooth       |
| MagWrite Gloss | - mirror smooth     |

- Adhesives/Primers:**
- for lightweight wallcoverings apply MagFix ready-mixed adhesive to the wall and apply pre-cut strips of wallcovering.
  - for heavyweight wallcoverings apply MagVOV ready-mixed adhesive to the wall and apply pre-cut strips of wallcovering.
  - apply a MagVOV adhesive directly to the wall and apply pre-cut strips of wallcovering.

Note: We strongly advise that you test in advance before any major installation.

- Hanging guide:**
- allow wallcoverings to adjust to room temperature
  - cut wallcovering into required lengths
  - ensure wallcoverings are hung using the recommended adhesive/primer option (see above)
  - pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops
  - apply the cut lengths, edge to edge, vertically or horizontally as required
  - apply MagLiner to the wall (shiny side to face the wall)
  - use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
  - use masking tape to secure if likely to slip during install
  - use a straight edge and sharp trimming knife at corners
  - do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
  - remove any excess paste with a damp sponge and wipe surface clean
  - leave to dry thoroughly (min 24 hrs)

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

## **MagScapes Limited**

5 Albemarle Way  
Clerkenwell  
London  
EC1V 4JB  
T: +44 (0) 800 804 4936  
W: [www.magscapes.com](http://www.magscapes.com)

### **MagLiner Finishes:**

- Wallcovering:** - paste any wallcovering or digital print directly on top of MagLiner by following manufacturers guides
- Dry Erase:** - for dry-erase finish apply laminate, carefully peel one corner back and apply to the wall in correct position
- slowly peel backing sheet away as you apply the material, flushing air bubbles and creases as you go
- Paint:** - apply all-purpose primer (Zinsser) allow to dry and then overpaint with any emulsion

**IMPORTANT:** MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.