



MagPaintable: USER GUIDE

Product	MagPaintable
Description	<p>MagPaintable is an easy to hang white primed paintable media offering a matt white canvas finish and receptive base to work with low power magnets. MagPaintable has features and finishing options that include:</p> <ul style="list-style-type: none"> - finish option a: use with any emulsion paint including blackboard - finish option b: use on top of MagLiner to boost receptivity
Receptivity Rating	<p>2/5 4/5 (with MagLiner)</p>
Weight	470 grammes per square metre
Fire Rating	Not Applicable
Roll Dimensions	120cm width x 6m / 12m lengths
Adhesive	MagFix adhesive
Warranty	7 Years
Maintenance:	- clean using a damp cloth
Magnet Usage:	<ul style="list-style-type: none"> - MagPaintable has low receptivity so works with MagLite low power magnet types - MagPlus are high power neodymium magnets for holding items - MagLite are low power sheet magnets for placement use
Health and Safety:	Warning - high power magnets can be dangerous if ingested and should not be used by children, always read safety information provided.
Classification:	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting:	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological:	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

MagPaintable: DECORATOR GUIDE

- Configuration** MagPaintable Wallcoverings may be hung in any of the configurations shown above.
- Tools:**
- A felt or sponge roller for paste application
 - Scissors or sharp blade knife
 - Straight edge
 - Soft wallpaper brush
 - Microfibre cloth or sponge
- Wall preparation:**
- ensure the plaster wall surface is clean, dry, sound, mirror smooth and free of paint or chemicals
 - best results will be obtained if the base plaster is sealed with a PVA sealer
 - where necessary fill holes with filler and use fine sandpaper to smooth
- Hanging guide:**
- allow wallcoverings to adjust to room temperature
 - cut wallcovering into required lengths
 - ensure wallcoverings are hung using MagFix or any high quality ready mixed adhesive.
 - pour adhesive into a pasting tray and using a roller apply paste evenly to the wall (soaking is not necessary) cover an area to allow for 1-2 drops (allow 5-7 mins for adhesive to become tacky)
 - apply the cut lengths, edge to edge, vertically or horizontally as required
 - apply MagPaintable to the wall (black side to face the wall)
 - use a soft clean wallpaper brush or microfibre cloth to flush out air bubbles and creases
 - use a straight edge and sharp trimming knife at corners
 - do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material
 - remove any excess paste with a damp sponge and wipe surface clean
 - leave to dry thoroughly (min 24 hrs)
- Finishing options:**
- Paint:**
- apply any emulsion or eggshell paint following manufacturers recommended instructions
- Removal:**
- gently strip away from wall using a scraper
 - MagPaintable will retain its receptive quality so may be re-used if undamaged on removal