

MAGLINER ROLL (MATT)

TECHNICAL SPEC

Product	MAGLINER (MATT)
Description	MAGLINER* has the highest receptivity and works with both MAGPLUS and MAGLITE magnets. The wallcovering has a versatile grey finish that can be used raw, primed and painted or covered with any wallpaper, fabric or digital print. The Liner can be applied to walls horizontally or vertically.
Receptivity Rating	5
Weight	1800 grammes per square metre
Fire Rating	EuroClass EN13501-I
Roll Width	61cm
Adhesive	MAGFIX Adhesive
Warranty	7 Years



Configuration	MAGLINER Wallcoverings may be hung in any of the configurations shown above.
Finishing	Once hung, the wallcovering can be used raw, primed and painted or covered with any wallpaper, fabric or digital print.
Hanging	<p>For best results, ensure the wall surface is clean, dry, sound, mirror smooth and free from paint or chemicals. Best results will be obtained if the base is sealed with a PVA sealer. Where necessary fill holes with filler and use fine sandpaper to smooth. Switch off the supply of electricity to sockets and light switches as a precaution. Switch off radiators during installation. Removal of radiators will aid installation if in the immediate area but not essential.</p> <p>Allow wallcoverings to adjust to room temperature and apply the correct side to face the wall - for MAGLINER it is the shiny side.</p> <p>Cut wallcovering into required lengths. Ensure all MagScapes wallcoverings are hung using MAGFIX Adhesive. Pour paste contents into paste tray and paste the wall. Soaking is not necessary. Apply the cut lengths, edge to edge, vertically or horizontally as required. Use a soft clean wallpaper brush or microfibre cloth to remove air bubbles and creases. Use a straight edge and sharp trimming knife at corners. Do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material. Remove any excess paste with a damp sponge and wipe surface clean. Leave to dry thoroughly (min 24 hrs). The wall is now ready to hold magnets and use pens.</p>

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

MagScapes Limited

5 Albemarle Way
Clerkenwell
London
EC1V 4JB
T: +44 (0) 800 804 4936
W: www.magscapes.com

Maintenance	MAGLINER may be cleaned using a damp micro fibre cloth. If used in an area of strong sun light move magnets regularly to avoid discolouring.
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl – do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.