

MagScapes Limited

5 Albemarle Way Clerkenwell London ECIV 4|B

T: +44 (0) 800 804 4936 W: <u>www.magscapes.com</u>

MAGWRITE ROLL (MATT / GLOSS) TECHNICAL SPEC

Product MAGWRITE (MATT / GLOSS)

Description MAGWRITE wallcovering has a highly durable dry erase PET laminate finish for use with dry

erase and chalk pens and can be applied to walls horizontally or vertically.

Receptivity Rating MAGWRITE has high receptivity so works with MAGLITE low and MAGPLUS high

power magnets

Weight 1900 grammes per square metre


Fire Rating EuroClass EN 13501-1


Roll Width 120cm

Adhesive MAGVOV Adhesive (non porous)

Warranty 7 Years













Configuration

MAGWRITE Wallcoverings may be hung in any of the configurations shown above.

Finishing

Once hung, the wallcovering can be used as a dry erase message area.

Hanging

For best results, ensure the wall surface is clean, dry, sound, mirror smooth and free from paint or chemicals. Best results will be obtained if the base is sealed with a PVA or all-purpose sealer. Where necessary fill holes with filler and use fine sandpaper to smooth. Switch off the supply of electricity to sockets and light switches as a precaution. Switch off radiators during installation. Removal of radiators will aid installation if in the immediate area but not essential.

For all writeable media, MagScapes recommend:

- hanging the material horizontally (where possible) to minimise pen use over seams
- placing wallcovering strip at optimal writing height (between waist and head height)
- using **EDGE**TRIM over seams where visible

Allow wallcoverings to adjust to room temperature and apply the correct side to face the wall - for MAGWRITE it is the black side. Cut wallcovering into required lengths. Ensure all MagScapes wallcoverings are hung using MAGFIX Adhesive. Pour paste contents into paste tray and paste the wall. Soaking is not necessary. Apply the cut lengths, edge to edge, vertically or horizontally as required. Use a soft clean wallpaper brush or microfibre cloth to remove air bubbles and creases. Use a straight edge and sharp trimming knife at corners. Do not puncture air bubbles and do not use metal or sharp objects (other than the cutting knife) on the surface when installing the material. Remove any excess paste with a damp sponge and wipe surface clean. Leave to dry thoroughly (min 24 hrs). The wall is now ready to hold magnets and use pens.

IMPORTANT: MagScapes wallcoverings can act as a conductor of electricity due to the ferrous content in the vinyl — do not allow it to come into contact with exposed wires, and take care when installing around electrical wiring and boxes. Turn electricity off.

MagScapes Limited

5 Albemarle Way Clerkenwell London ECIV 4|B

T: +44 (0) 800 804 4936 W: <u>www.magscapes.com</u>

Maintenance MAGWRITE may be cleaned using a damp micro fibre cloth. If used in an area of strong

sun light move magnets regularly to avoid discolouring. Change erasers or towels once dirty. For daily cleaning, or as required, wash the surface with water and rinse thoroughly.

Remove remaining marks with spray cleaner.

MagScapes recommend Artline, Pentel dry-erase markers for best results. Use microfibre

towel and whiteboard spray for cleaning. NEVER use felt or abrasive cleaners.

Health & Safety This product is classified as non-hazardous and therefore does not require any special

handling. This product does not require special labelling.

Fire Fighting Any extinguishing media are suitable. Wear self contained breathing apparatus, protective

clothing and full face mask. Fumes should be ventilated immediately due to possible liberation

of noxious gases.

Ecological This product is not bio-degradable. Dispose of in accordance with Local Authority

regulations or via an authorised contractor.