

















Vented Control Valve Features and Breakdown

Model	Features	Options	Burner Sizes
MA & MAHC-GC 	<ul style="list-style-type: none"> *Manual On/Off w/ Knob or Wrench Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 300° *90,000 BTU's (NG/LP) - MA *240,000 BTU's (NG/LP) - MAHC 	N/A	MA 2 Burner/Glass/Kiva – 18"-42" (NG/LP) 3 Burner – 18"-30" (NG/LP) MAHC Jumbo/Jumbo Slimline 24"-84" (NG/LP)
SPQMKN & SPQMKL 	<ul style="list-style-type: none"> *Standing Pilot System *Manual On/Off Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 300° *(NG) 90,000 BTU's *(LP) 90,000 BTU's 	N/A	2 Burner/Glass/Kiva – 18"-30" (NG) 18"-42" (LP) 3 Burner – 18"-24" (NG) 18"-36" (LP) Jumbo/Jumbo Slimline N/A (NG) N/A (LP)
HCSPK-N & HCSPK-LP 	<ul style="list-style-type: none"> *Standing Pilot System *Manual On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 250° *(NG) 124,000 BTU's *(LP) 200,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote *GCWS (On/Off) Wall Switch 	2 Burner/Glass/Kiva – 18"-42" (NG) 18"-60" (LP) 3 Burner – 18"-42" (NG) 18"-42" (LP) Jumbo/Jumbo Slimline 24"-30" (NG) 24"-48" (LP)
MVQMKN & MVQMKL 	<ul style="list-style-type: none"> *Standing Pilot System *On/Off Operations ONLY *Low Profile Design *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-5" W.C. 70,000 BTU's *(LP) 8"-12" W.C. 110,000 BTU's 	<ul style="list-style-type: none"> *GCRK (On/Off) remote *GCWS (On/Off) Wall Switch 	2 Burner/Glass/Kiva – 18"-30" (NG) 18"-42" (LP) 3 Burner – 18"-24" (NG) 18"-36" (LP) Jumbo/Jumbo Slimline N/A (NG) 24"-30" (LP)
MMVKR-NG & MMVKR-LP	<ul style="list-style-type: none"> *Standing Pilot System *Variable Flame Height *Low Profile Design 	N/A	2 Burner/Glass/Kiva – 18"-42" (NG) 18"-42" (LP) 3 Burner –

	<p>*Max Inlet 14" W.C. *Valve Temp Rating 225° *(NG) 7" W.C. 120,000 BTU's *(LP) 7"-14" W.C. 120,000 BTU's</p>		<p>18"-42" (NG) 18"-42" (LP) Jumbo/Jumbo Slimline 24" – 30" (NG) 24"-30" (LP)</p>
<p>HCMVQMKN & HCMVQMKLP</p> 	<p>*Standing Pilot System *High Volume Output Millivolt System *On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-5" W.C. 370,000 BTU's *(LP) 8"-12" W.C. 560,000 BTU's</p>	<p>*GCRK (On/Off) remote *GCWS (On/Off) Wall Switch</p>	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP) Jumbo/Jumbo Slimline 24"-108" (NG) 24"-120" (LP)</p>
<p>MVKEIKN & MVKEIKLP</p> 	<p>*Non-Standing Pilot *2-D Cell Battery Electronic Ignition *Pilot on Demand System *On/Off Operations ONLY *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 88,000 BTU's *(LP) 8"-14" W.C. 110,000 BTU's</p>	<p>*GCRK (On/Off) remote *GCWS (On/Off) Wall Switch</p>	<p>2 Burner/Glass/Kiva – 18"–42" (NG) 18"–42" (LP) 3 Burner – 18"-30" (NG) 18"-36" (LP) Jumbo/Jumbo Slimline N/A (NG) 24"-30" (LP)</p>
<p>EIS & EIS-LP</p> 	<p>*Non-Standing Pilot *Pilot on Demand System *24V Electronic Ignition *On/Off Operations ONLY *In-Wall Design *6'-10' Pilot Assembly *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 200,000 BTU's *(LP) 8"-14" W.C. 320,000 BTU's</p>	<p>*GCRK (On/Off) remote *GCWS (On/Off) Wall Switch *WBPB12/24</p>	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP) Jumbo/Jumbo Slimline 24"-60" (NG) 24"-96" (LP)</p>
<p>EIS-350 & EIS-350-LP</p> 	<p>*Non-Standing Pilot *Pilot on Demand System *24V Electronic Ignition *On/Off Operations ONLY *In-Wall Design *6'-10' Pilot Assembly *Max Inlet 14" W.C. *Valve Temp Rating 175° *(NG) 3"-7" W.C. 350,000 BTU's *(LP) 8"-14" W.C. 560,000 BTU's</p>	<p>*GCRK (On/Off) remote *GCWS (On/Off) Wall Switch *WBPB12/24</p>	<p>2 Burner/Glass/Kiva – 18"–60" (NG) 18"–42" (LP) 3 Burner – 18"–42" (NG) 18"–42" (LP) Jumbo/Jumbo Slimline 24"-120" (NG) 24"-120" (LP)</p>

 <p>WBECs</p>	<ul style="list-style-type: none"> *Hot Surface Ignition System *Pilot on Demand System *LED Diagnostics *12V Electronic Ignition *On/Off Operations ONLY *24" Pilot Assembly *CSA Certified Control System *Max Inlet 14" W.C. *Valve Temp Rating 175° *265,000 BTU (NG/LP) 	<ul style="list-style-type: none"> *GCRK-110 (On/Off) remote *WBPB12/24 	<ul style="list-style-type: none"> *All Fire-Pits *All Fire-tables *Outdoor Burners
<p>Model</p>	<p>Features</p>	<p>Options</p>	<p>Application</p>
 <p>GCWS</p>	<ul style="list-style-type: none"> *Basic On/Off Operations *Rocker Switch & Cover Included *15' 10-2 low voltage wire 	<p>N/A</p>	<ul style="list-style-type: none"> *MVQMKN/LP *HCMVQMKN/LP *ALL EIS Configurations
 <p>GCRK</p>	<ul style="list-style-type: none"> *Basic On/Off Operations *RF Transmitter & Receiver *LCD Temp Display *Includes Batteries & Wall Plate 	<p>N/A</p>	<ul style="list-style-type: none"> *MVQMKN/LP *HCMVQMKN/LP *ALL EIS Configurations
 <p>GCRK-110</p>	<ul style="list-style-type: none"> *Basic On/Off Operations *110V Plug-In *RF Transmitter & Receiver *Includes Batteries 	<p>N/A</p>	<ul style="list-style-type: none"> *WBECs
 <p>WBPB-12/24</p>	<ul style="list-style-type: none"> *Bluetooth Wi-Fi & Manual Control *Connect with Home Automation OR Weather Smart App *24V System 	<p>N/A</p>	<ul style="list-style-type: none"> *ALL EIS Configurations *WBECs