



TECHNICAL SPECIFICATIONS:

- 20,000BTU/HR (HI) 15,000BTU/HR (LO)
- MANIFOLD PRESSURE: NG 6.2" W.C. (HI), 3.0" W.C. (LO)
- GAS SUPPLY PRESSURE: NG 7.0" W.C. (MIN), 14.0" W.C. (MAX)
- ELECTRICAL SUPPLY: 24 VOLTS, 0.8 AMPS

PERSPECTIVE

- DIRECT SPARK IGNITION WITH 3-TRY LOCK OUT & AUTOMATIC RE-LIGHT

WARRANTY:

- 3 YEARS ON CERAMIC BURNER
- 1 YEAR ON ALL OTHER PARTS

12.34 10.64 17.25

END CLEARANCES



SIDE ELEVATION

FRONT ELEVATION MODEL HAB-M20

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-007.



5029-007 REVISION DATE 12/06/2017