

MINIATURE CIRCUIT BOARD JACKS 70/370 SERIES

CBJ70 Shown

TWINAX/TRIAX TRB CONCENTRIC CIRCUIT BOARD JACK

3-lug
2-lug
4-lug
(TRT) Threaded

CBJ70
CBJ70TL
CBJ70FL
CBJ370

CBBJ79 Shown

TWINAX/TRIAX TRB NON-INSULATED CONCENTRIC FEMALE 3-LUG BULKHEAD MOUNT

3-lug
2-lug
4-lug
Threaded

CBBJ79
CBBJ79TL
CBBJ79FL
CBBJ379

Mounting Hole: D3.109

MODEL NO.	LTR CODE	A DIM	B DIM	C DIM	D DIM
CBJR70	-	.24	.050	.090	.0625
CBJR70A	A	.34	.058	.090	.070

TWINAX/TRIAX TRB RIGHT ANGLE CONCENTRIC CIRCUIT BOARD JACK

3-lug

CBJR70
CBJR70A

TWINAX/TRIAX TRB INSULATED CONCENTRIC FEMALE 3-LUG BULKHEAD MOUNT

3-lug

CBBJ74

Mounting Hole: D2.109

MODEL NO.	LTR CODE	A DIM	B DIM	C DIM	D DIM	E DIM
CBBJR79	-	.24	.565	.050	.090	.0625
CBBJR79A	A	.34	.665	.058	.090	.070

RIGHT ANGLE CIRCUIT BOARD BULKHEAD JACK

Standard Version

3-lug
2-lug
4-lug
Threaded

CBBJR79
CBBJR79TL
CBBJR79FL
CBBJR379

Add "A" for tall versions
example: **CBBJR79A**

See diagram above

* 305-0789

Mounting Hole: D3.125

MODEL NO.	LTR CODE	A DIM	B DIM	C DIM	D DIM
CBBJR74	-	.345	.778	.050	.0625
CBBJR74A	A	.445	.878	.058	.070

MAX PANEL THICKNESS .140

RIGHT ANGLE INSULATED CIRCUIT BOARD BULKHEAD JACK

Insulated Version

3-lug
2-lug
4-lug
Threaded

CBBJR74
CBBJR74TL
CBBJR74FL
CBBJR374

Add "A" for tall versions example: **CBBJR74A**

Mounting Hole: D2.140

"D" mounting holes see page 63.