

PA2220CA Air curtain

Article Number: 8659



Description

Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting
- Lengths: 1, 1,5 and 2 m

PA2220C is a compact air curtain, suitable for most small entrances. The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation	
Type of installation	Horizontal
Maximum installation height	2,200 mm
Nominal data	
Heating type	None
Color casing	Traffic white
Color casing, NCS	NCS S 0500-N
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP21
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,050 mm
Height	209 mm
Depth	345 mm
Weight	32 kg
Air flow	
Air flow	2,400; 2,000; 1,800 m³/h
Sound data	
Sound level	53; 48; 43 dB(A)
Sound power level LWA	68 dB(A)
Motor/control supply	
Control/motor supply	230 V
Phase(s), motor	1~
Control/motor current	0.9 A
Input power (P1), motor	200 W
Maximum fan impeller speed	1,360 r.p.m.

Accessories

PA2DR Remote + door contact (15662)
PA2PF20 Pendulum brackets (19417)
PAMLK PC board alarm (18690)

PA2P20 Pendulum bar (19569)
PA34TR20 Threaded rods (18057)

Documents

Catalogue pages PA2200C

Manual motor alarm board PAMLK

Manual door switch control PA2DR

Manual brackets PA2PF, PA2P, threaded bars PA34TR

Manual PA2200C

WIRING DIAGRAM PA2200C.PDF

PA2220CE_CA-2D.DWG

PA2220CA-3D.dxf

Declaration of conformity Air curtains