

PA2210CE08 Air curtain

Electrical heat 8kW, L=1m

Item Number: 19422



Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances.

The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation		
Type of installation	Horizontal	
nan	2,200	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	1,050	mm
Height	209	mm
Depth	345	mm
Weight	19	kg

Air flow

Air flow	0.25; 0.3333; 0.2778	m³/s
----------	----------------------	------

Sound data

Sound level	51; 47; 42	dB(A)
-------------	------------	-------

Sound power level LWA	67	dB(A)
-----------------------	----	-------

Motor/control supply

Control/motor supply	230	V
----------------------	-----	---

Control/motor current	0.45	A
-----------------------	------	---

Input power (P1), motor	110	W
-------------------------	-----	---

Electric heat

Current heating	11.5; 7.2	A
-----------------	-----------	---

Voltage heating	400	V
-----------------	-----	---

Input power, heater	8; 5	kW
---------------------	------	----

Phase(s)	3~	
----------	----	--

Temperature rise, maximum heat output, highest airflow	20	°C
--	----	----

Temperature rise, maximum heat output, lowest airflow	27	°C
---	----	----

Accessories

- PA2DR Remote + door contact (15662)
- PA2PF15 Pendulum brackets (19415)
- PAMLK PC board alarm (18690)
- PA2P15 Pendulum bar (19568)
- PA34TR15 Threaded bars (18056)