

PA2215CE08 Air curtain

Electrical heat 8kW, L=1.5m

Item Number: 8158



Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances.

The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation	
Type of installation	Horizontal
nan	2,200 mm
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,560 mm
Height	209 mm
Depth	345 mm
Weight	26 kg

Air flow

Air flow	0.5; 0.4028; 0.3194	m³/s
----------	---------------------	------

Sound data

Sound level	52; 48; 40	dB(A)
-------------	------------	-------

Sound power level LWA	67	dB(A)
-----------------------	----	-------

Motor/control supply

Control/motor supply	230	V
----------------------	-----	---

Control/motor current	0.48	A
-----------------------	------	---

Input power (P1), motor	110	W
-------------------------	-----	---

nan	1,260	r.p.m.
-----	-------	--------

Electric heat

Current heating	11.6; 10	A
-----------------	----------	---

Voltage heating	400	V
-----------------	-----	---

Input power, heater	8; 4	kW
---------------------	------	----

Phase(s)	3~	
----------	----	--

Temperature rise, maximum heat output, highest airflow	13	°C
--	----	----

Temperature rise, maximum heat output, lowest airflow	21	°C
---	----	----