

# PA2215CE12 Air curtain

Electrical heat 12kW, L=1.5m

Item Number: 8668



## Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m\*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances.

The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

\*) Recommended installation height varies depending on the relevant premises.



## Technical parameters

Installation		
Type of installation	Horizontal	
nan	2,200	mm
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30	°C
Dimensions and weights		
Length	1,560	mm
Height	209	mm
Depth	345	mm
Weight	28	kg

**Air flow**

Air flow	0.5; 0.4028; 0.3194	m <sup>3</sup> /s
----------	---------------------	-------------------

**Sound data**

Sound level	52; 48; 40	dB(A)
-------------	------------	-------

Sound power level LWA	67	dB(A)
-----------------------	----	-------

**Motor/control supply**

Control/motor supply	230	V
----------------------	-----	---

Control/motor current	0.48	A
-----------------------	------	---

Input power (P1), motor	110	W
-------------------------	-----	---

nan	1,260	r.p.m.
-----	-------	--------

**Electric heat**

Current heating	17.3; 11.5	A
-----------------	------------	---

Voltage heating	400	V
-----------------	-----	---

Input power, heater	12; 8	kW
---------------------	-------	----

Phase(s)	3~	
----------	----	--

Temperature rise, maximum heat output, highest airflow	20	°C
--	----	----

Temperature rise, maximum heat output, lowest airflow	31	°C
---	----	----