

PA220CE10 Air curtain

Electrical heat 10kW, L=2m

Item Number: 8454



Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances.

The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation	
Type of installation	Horizontal
nan	2,200 mm
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,050 mm
Height	209 mm
Depth	345 mm
Weight	34 kg

Air flow

Air flow	0.6667; 0.5556; 0.5	m³/s
----------	---------------------	------

Sound data

Sound level	53; 48; 43	dB(A)
-------------	------------	-------

Sound power level LWA	69	dB(A)
-----------------------	----	-------

Motor/control supply

Control/motor supply	230	V
----------------------	-----	---

Control/motor current	0.9	A
-----------------------	-----	---

Input power (P1), motor	200	W
-------------------------	-----	---

nan	1,360	r.p.m.
-----	-------	--------

Electric heat

Current heating	14.4; 12.5	A
-----------------	------------	---

Voltage heating	400	V
-----------------	-----	---

Input power, heater	10; 5	kW
---------------------	-------	----

Phase(s)	3~	
----------	----	--

Temperature rise, maximum heat output, highest airflow	12	°C
--	----	----

Temperature rise, maximum heat output, lowest airflow	17	°C
---	----	----