

Description

Stylish air curtain for entrances, with remote and integrated control

- Recommended installation height 2,2 m*
- Horizontal mounting

PA2200C is a compact air curtain, suitable for most small entrances. The air curtain has an integrated control system and can also be remotely controlled which makes it very easy to use.

*) Recommended installation height varies depending on the relevant premises.



Technical parameters

Installation	
Type of installation	Horizontal
nan	2,200 mm
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,050 mm
Height	209 mm
Depth	345 mm
Weight	36 kg
Air flow	
Air flow	0.6667; 0.5556; 0.5 m³/s
Sound data	
Sound level	53; 48; 43 dB(A)
Sound power level LWA	69 dB(A)
Motor/control supply	
Control/motor supply	230 V
Control/motor current	0.9 A
Input power (P1), motor	200 W
nan	1,360 r.p.m.

Electric heat		
Current heating	23.1; 20	A
Voltage heating	400	V
Input power, heater	16; 10	kW
Phase(s)	3~	
Temperature rise, maximum heat output, highest airflow	20	°C
Temperature rise, maximum heat output, lowest airflow	27	°C

Parameter	
Power	16.00 kW
Air flow	0.67 m³/s
Inlet air temperature	20.0 °C
Outlet air temperature	40.0 °C
Inlet air humidity	70 % r.H
Outlet air humidity	22 % r.H

Accessories

[PA2DR Remote + door contact \(15662\)](#)
[PA2PF20 Pendulum brackets \(19417\)](#)
[PAMLK PC board alarm \(18690\)](#)

[PA2P20 Pendulum bar \(19569\)](#)
[PA34TR20 Threaded bars \(18057\)](#)

Documents

[Catalogue pages PA2200C](#)
[MA_FRICO_PA2200C_GB.PDF](#)
[Declaration of Conformity PA2200C](#)
[UKCA Declaration of Conformity Air Curtains](#)
[WIRING DIAGRAM PA2200C.PDF](#)