

12"

## SPECIFICATIONS

Blade Color	Black
Brand	Schaefer
Cfm (free Air)	TBD
Cfm (with 25' Of Duct)	TBD
Drive	Direct
Enclosure	TEAO
Frame Size	48
Housing Material	Polyethylene
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	15 3/4" x 16 3/4"
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	TBD
Cord	Not included

Diameter (inches)	12
Frequency (hz)	60
Guard Color	Black
Nameplate Amps	3.8/1.9
Number Of Wings	6
Bess Lab Performance Test #	96221
Operating Temperature (low) F	TBD
Power (hp)	1/3
Product Dimensions (l X W X H Inches)	TBD
Product Net Weight (lbs)	31
Voltage	115/230
Blade Material	Polyethylene
Cfm (high)	TBD
Product Color	White
Product Shipping Dimensions (in)	20 X 19 X 23

Speed Control Compatible?	Yes
Able To Ship Small Parcel	Yes
Cfm Range (free Air)	1001 - 2500
Distinguishing Feature	Highly Corrosion Resistant
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Sound Level (dda @ 10')	63.3
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	7.3
Cfm (@0.05")	1540

16"

## SPECIFICATIONS

Blade Color	Black
Brand	Schaefer
Cfm (free Air)	TBD
Cfm (with 25' Of Duct)	TBD
Drive	Direct
Housing Material	Polyethylene
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	19 1/2" x 20 1/2"
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	TBD
Cord	Not included
Diameter (Inches)	16

Frequency (hz)	60
Guard Color	Black
Nameplate Amps	3.8/1.9
Number Of Wings	3
Bess Lab Performance Test #	96220
Operating Temperature (low) F	TBD
Power (hp)	1/3
Product Net Weight (lbs)	41
Voltage	115/230
Blade Material	Polyethylene
Cfm (high)	TBD
Product Color	White
Product Shipping Dimensions (in)	25 X 24 X 26
Speed Control Compatible?	Yes

Able To Ship Small Parcel	Yes
Cfm Range (free Air)	2501 - 5000
Distinguishing Feature	Highly Corrosion Resistant
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (Inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	9.2
Cfm (@0.05")	3090

20"

## SPECIFICATIONS

Blade Color	Black
Brand	Schaefer
Cfm (free Air)	TBD
Cfm (with 25' Of Duct)	TBD
Drive	Direct
Enclosure	TEAO
Frame Size	48
Housing Material	Polyethylene
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	23 1/2" x 24 3/4"
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	TBD
Cord	Not included

Diameter (inches)	20
Frequency (hz)	60
Guard Color	Black
Nameplate Amps	3.8/1.9
Number Of Wings	3
Bess Lab Performance Test #	96219
Operating Temperature (low) F	TBD
Power (hp)	1/3
Product Net Weight (lbs)	48
Voltage	115/230
Blade Material	Polyethylene
Cfm (high)	TBD
Product Color	White
Product Shipping Dimensions (in)	29 x 29 x 29
Speed Control Compatible?	Yes

Able To Ship Small Parcel	Yes
Cfm Range (free Air)	2501 - 5000
Distinguishing Feature	Highly Corrosion Resistant
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	12.8
Cfm (@0.05")	3530

## 20" HL

### SPECIFICATIONS

Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	3520
Drive	Direct
Housing Material	Polyethylene
Phase	1
Rough-in Dimensions	23 1/2" x 24 3/4"
Speeds	1
Vfd Compatible	No
Cord	Not included
Diameter (inches)	20

Frequency (hz)	60
Guard Color	Black
Nameplate Amps	3.6/1.8
Number Of Wings	3
Power (hp)	1/3
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	51
Performance Test #	0772
Voltage	115/230
Maximum Rpm	1725
Air Velocity (@ 5 Times Diameter)	TBD
Blade Material	Aluminum



Product Color	Gray
Speed Control Compatible?	No
Blade Pitch (degrees)	21
Cfm Range (free Air)	2501 - 5000
Distinguishing Feature	Hazardous Location Rated
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Thermal Protection	Yes
Country Of Origin	US
Guard Spacing (inches)	1 - 2
Housing Color	Gray