Treegator Installation Instructions

Produced by Grower's Solution

If you have any questions or comments, feel free to contact us.

Phone: 1-931-528-3390

Toll-Free: 1-866-928-3390

Fax: 1-775-640-4505

crf@growerssolution.com

or visit us at:

www.growerssolution.com

More information and tutorials are available at:

www.growerslearning.com

UST ZIP, FILL, AND WALK AWAY!

Just wrap our 20 Gallon Treegator® around a tree, zip the two sides together, and fill it with water - that's it!

Step-by-step Treegator® Original installation instructions:

- Place back of bag against trunk, with zippers on the uphill side of tree.
- Wrap both sides around trunk until zippers meet together:
 Single bag fits 1" to 4" caliper (dia.) trees.
 Two bags zipped together fits up to 8"
- caliper (dia.) trees.Zip both sides of bag together from bottom to top.
- Lift up tag at top of bag to expose fill opening.
- For added root growth benefits, drop in 1 (one) <u>ROOTS®</u> <u>Solupak™</u> into fill opening.
- Insert water hose (up to 3" dia.), into fill opening, turn on water supply and begin filling.
- bag only to approximately 1/4 capacity, then proceed to Step 3.

STEP 1



STEP 2





STEP 3



- Gently lift up on the two black straps at top of bag in order to fully expand bottom.
- If desired, add premixed water soluble nutrients, or
 <u>Hydretain® ES Plus</u>
 Root Zone Moisture
 Manager.
- NOTE: Premix nutrients in separate container. (This step is not necessary with <u>ROOTS®</u> <u>SolupakTM</u>)
- Fill with water to desired level.

 > Single bag: Max. capacity of approximately 20 Gallons

 > Two bags = Max. capacity of approximately 50 Gallons
- Treegator® Original will be empty in approx. 5 to 9 hours.
- For most newly planted trees (1" to 3" caliper), follow an initial fill schedule of 1 application per week.

STEP 4



*Before installation, please be sure to read and comply with the recommended <u>Handling Precautions</u> for this product.