Self-Contained Datalogger













Scan this QR code to view our product demo.

Datalogger without docking station. LCDs do not work reliably below 20 or above 51°C

Logs up to 16,000 readings

Self-Contained RH/Temperature Datalogger. Place the Datalogger in it's docking station and program it using your computer and the Datalogger's own software. Set to read temperature and RH in intervals of 1 second to 2 hours and for visual min/max alarms if desired. Choose to begin recording immediately, at a predetermined time, or via external activation. The Datalogger is now ready for use in electronic, food and drug production, shipping and storage, greenhouses, refrigerators, art galleries, museums, HVAC, process control, meteorology, agriculture, or labs. Datalogger comes with built in sensor, wall mount and LEDs that flash as it samples. Features a direct display of current ambient temperature and RH. Takes up to 16,000 readings. An internal clock stores the date and time with each reading and non-volatile memory insures that data will not be lost even if the battery dies or is removed. When monitoring is complete simply return the Datalogger to its docking station, connect the station to your computer using the computer cable included, and start to download and view results on your computer using the free downloadable software. Set includes one datalogger, docking station with computer cable, sfree downloadable software, battery and instructions. N.I.S.T. Traceable Calibration Report available.

DIM: $3'' \times 2'' \times 7/8''$ (76 × 51 × 22 mm).

WEIGHT: 3 oz (85 g).

No.	Description
800054 800054C	Self-Contained Datalogger Self-Contained Datalogger Calibrated
800055	Additional Temp/RH Datalogger (without Docking Station) w/LCD
800055C	Additional Temp/RH Datalogger (without Docking Station) w/LCD Calibrated

Model:	800054 Temperature/ RH Datalogger w/LCD set	
Temperature range	-40 to 185°F / -40 to 85°C	
Temp Resolution	0.1°	
Temp Accuracy	±0.6°C (-20 to 50°C), ±1.2°C (-40 to 20°C & 51 to 85°C)**	
RH range	0 to 100%	
RH resolution	0.1%	
RH accuracy	±5% RH	
Display**	LCD	
Maximum Memory	16,000	
Water Resistance*	Yes	