# IGL COATINGS™ ECOCOAT KENZO K1 BASE

Material no.

Specification 154343 Revision date 05.09.2022

Version **1.00** Page 1 of 6



# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ Ecocoat Kenzo K1 Base

FUNCTION : Hydro- & oleophobic and easy-clean agent surface modifier and gloss enhancer

COMPANY : Ominent Sdn Bhd

ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam,

Selangor.

PHONE : +60355690980

EMAIL ADDRESS : regulations@iglcoatings.com

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

**Health hazards** 

Skin Irritation Category 2
Eye Damage Category 1

**Environmental hazards** 

Chronic Aquatic hazard Category 3

# 2.2 Label Elements

Regulation (EC) No. 1272/2008



# Signal word

Danger

# **Hazard statements**

H315 Causes skin irritation
H318 Causes serious eye damage

H412 Harmful to aquatic life with long lasting effects

# **Precautionary statements**

P264 Wash exposed skin thoroughly after handling.

P273 Avoid release to the environment.
P280 Wear personal protective equipment.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P354+P338 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P332+P317 If skin irritation occurs: Get medical help.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place.

P501 Dispose of contents in accordance with local/regional/federal regulations.

# 2.3 Other hazards:

Product hydrolyses, producing Methanol (CAS no. 67-56-1). Methanol is highly flammable.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name			Quantity
	EC No.	Index No.	REACH No.	
	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
2530-83-8	3-Glycidyloxypropyltrimethoxysilane			50-70%
	219-784-2	Not applicable	01-2119513212-58-0000	

# IGL COATINGS™ ECOCOAT KENZO K1 BASE



 Specification
 154343
 Revision date
 05.09.2022

 Version
 1.00
 Page
 2 of 6



	Eye Dam. 1: H318; Ac	Eye Dam. 1: H318; Aquatic chronic 3: H412		
63148-62-9	Dimethyl siloxane	Dimethyl siloxane		
	613-156-5	Not applicable	Not applicable	
	Not Classified			
2943-75-1	Triethoxy-n-octylsilar	Triethoxy-n-octylsilane		
	220-941-2	Not applicable	01-2119972313-39-0000	
	Skin Irr. 2: H315; Aqu	Skin Irr. 2: H315; Aquatic chronic 2: H411		
5593-70-4	Titanium tetrabutano	Titanium tetrabutanolate		
	227-006-8	Not applicable	01-2119967423-33-0000	
	Flam. Liq 3: H226; Ski	Flam. Liq 3: H226; Skin Irr. 2: H315; Eye Dam. 1: H318; STOT SE 3: H335		

#### 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

#### **General Information**

Take persons to a safe place. Observe self-protection for first aid.

#### **After Inhalation**

Keep the patient calm. If unconscious, place in stable sideway position.

# After contact with skin

Remove contaminated or soaked clothing. Wash off immediately with soap and plenty of water.

In the event of a visible skin change or other complaints, seek medical advice.

#### After contact with eyes

Rinse immediately with plenty of water for 10-15 minutes. Remove contact lenses, if presence and easy to do. Seek medical advice in case of continuous irritation.

# After swallowing

If conscious, give several small portions water to drink. Do not induce vomiting.

Seek medical advice immediately and clearly identify substance.

# 4.2. Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

# 4.3. Indication of any immediate medical attention and special treatment needed

In case of contact with water materials splits off (also in gastrointestinal tract) methanol in larger amounts; therefore consider poisoning on methanol and also observe known period of latency of several days.

#### 5. FIRE-FIGHTING MEASURES

# 5.1 Extinguishing media

Water mist, extinguishing powder, alcohol resistant foam, carbon dioxide, sand.

# 5.2 Unsuitable extinguishing media

Water spray, water jet.

# 5.3 Special hazards arising from the substance or mixture

No data available.

#### **5.4 Advise for firefighters**

Use respiratory protection independent of recirculated air.

# 5.5 Unusual Fire Hazards:

None

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Keep unprotected persons away. Avoid contact with eyes and skin.

Avoid inhaling mists and vapours. If material is released indicate risk of slipping.

# 6.2 Environmental precautions

Prevent material from entering surface water, drains or sewers and soil.

Contain any fluid that runs out using suitable material (e.g. earth).

Retain contaminated water/extinguishing water. Dispose of in prescribed containers.

# IGL COATINGS™ ECOCOAT KENZO K1 BASE

Material no.

Specification 154343 Revision date 05.09.2022

Version **1.00** Page 3 of 6



# 6.3 Methods and material for containment and cleaning up

Do not flush away with water.

For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose into suitable containers. Clean any slippery coating that remains using a detergent/soap solution. Exhaust vapour.

#### 6.4 Reference to other sections

Safe handling: Refer to section 7

Personal protection equipment: Refer to section 8

Disposal: Refer to section 13

#### 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Wear personal protection equipment (Refer to section 8).

Ensure adequate ventilation.

Keep away from incompatible substances in accordance with section 10.

Spilled substance increases risk of slipping.

# Precaution against fire and explosion

Product can separate methanol. Flammable vapor may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

# 7.2 Conditions for safe storage, including any incompatibilities

# Condition for storage rooms and vessels

Make sure there is no possibility of entering the ground.

# Advice for storage of incompatible materials

Not applicable

# **Further information for storage**

Protect against moisture.

Store in original container only.

Keep container tightly closed and store in a cool, well ventilated place.

# 7.3. Specific end use(s)

No data available.

# 8. EXPOSURE CONTROL/PERSONAL PROTECTION

# 8.1 Control parameters

# Ingredients with limit values that require monitoring at the workplace:

No information available

# 8.2 Exposure Control

#### 8.2.1 Exposure in the workplace limited and controlled

# **General protective and hygienic measures**

Avoid contact with eyes and skin.

Do not inhale vapours.

Do not eat, drink, or smoke when handling.

# 8.2.2 Personal protective equipment:

# **Respiratory protection**

In case of long and strong exposure, use mask with an ABEK filter.

#### **Hand protection**

Use protective gloves made of butyl rubber. Gloves suitable for up to 60 minutes' use. The selection of appropriate gloves not only depends on the material, but also on the other quality characteristics, and may vary depending on the manufacturer. Please observe information from your glove supplier in terms of permeability and breakthrough time.

# **Eye protection**

Tight fitting protective goggles.

# Skin protection

Protective clothing

# IGL COATINGS™ ECOCOAT KENZO K1 BASE

Material no.

Specification 154343 Revision date 05.09.2022

Version **1.00** Page 4 of 6



#### 8.2.3 Exposure to the environment limited and controlled

Prevent materials from entering surface waters and soil.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state / form : Liquid Colour : Clear

pH : Not applicable Melting point : Not applicable Boiling Point : 180-220 °C

Density :  $1.068 \text{ g/cm}^3 \text{ (at } 25^{\circ}\text{C)}$ 

Flash Point : 150°C

Solubility in Water : Virtually insoluble

# 10. STABILITY AND REACTIVITY

**10.1 Reactivity**: Not classified as a reactivity hazard.

**10.2 Chemical stability**: Stable under normal condition.

10.3 Possibility of hazardous reactions: No data available.

**10.4 Conditions to avoid**: Moisture, heat, open flames and other sources of ignition.

**10.5 Incompatible materials**: Oxidising agents, acids, water.

**10.6 Hazardous decomposition products**: When heated to temperatures above 150°C (300 F) in the presence of air, product can form formaldehyde vapours. Hazardous decomposition products will be formed upon contact with water or humid air.

# 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

Exposure route	Endpoint	Value	Species	Source
Oral	LD50	6871 mg/kg	Rat	ECHA
Dermal	LD50	4854 mg/kg	Rat	ECHA

**Skin corrosion/irritation:** Causes skin irritation.

**Serious eye damage/eye irritation:** Causes serious eye damage.

Respiratory or skin sensitization: No data available.

Summary of evaluation of the CMR properties: No data available.

Specific target organ toxicity – single exposure: No data available.

Specific target organ toxicity – repeated exposure: No data available.

Aspiration hazard: No data available.

# 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No data available.

# 12.2 Process of degradability

No data available.

# 12.3 Bioaccumulative potential

No data available.

# 12.4 Mobility in soil

No data available.

#### 12.5 Results of PBT and vPvB Assessment

No data available.

# 12.6 Other adverse effects

No data available.

#### 13. DISPOSAL CONSIDERATION

Waste treatment methods

**Material:** 



Material no.

Specification 154343 Revision date 05.09.2022 Version 1.00 5 of 6 Page



#### Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator. Observe local/state/federal regulations.

# **Uncleaned packaging**

Recommendation:

Completely discharged containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or reused. Observe local/state/federal regulations.

# 14. TRANSPORT INFORMATION

#### **14.1 IATA-DGR**

**UN** number : -

UN proper shipping name : Non dangerous goods

Transport hazard class(es) Packing group : -Environmental hazards : -

Special precautions for user : No data available.

Remarks : -

#### 14.2 IMDG-Code

**UN** number

UN proper shipping name : Non dangerous goods

Transport hazard class(es) : -Packing group : -Environmental hazards Marine pollutant : No **EmS Code** : -

#### 15. REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **US Federal Regulations**

# **US. Toxic Substances Control Act (TSCA)**

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

# Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous **Substance List**

None present or none present in regulated quantities.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous **Substance**

None present or none present in regulated quantities.

# Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release **Inventory (TRI) Reporting**

None present or none present in regulated quantities.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

# **US. State Regulation**

# **US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

# **EU Regulation**

# IGL COATINGS™ ECOCOAT KENZO K1 BASE

Material no.

Specification 154343 Revision date 05.09.2022

Version **1.00** Page 6 of 6



EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

# 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### 16. OTHER INFORMATION

#### **Further information**

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.

# IGL COATINGS™ ECOCOAT KENZO K1 TOP

Material no.

Specification 154344 Revision date 05.09.2022

Version **1.00** Page 1 of 6



# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ Ecocoat Kenzo K1 Top

FUNCTION : Hydro- & oleophobic and easy-clean agent surface modifier and gloss enhancer

COMPANY : Ominent Sdn Bhd

ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam,

Selangor.

PHONE : +60378310980

EMAIL ADDRESS : regulations@iglcoatings.com

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

**Physical hazards** 

Flammable Liquid Category 4

# 2.2 Label Elements

Regulation (EC) No. 1272/2008

This product is not entitled for any hazard pictogram under GHS criteria.

# Signal word

Warning

# **Hazard statements**

H227 Combustible liquid

# **Precautionary statements**

P210 Keep away from open flames and hot surfaces. No smoking.

P280 Wear protective gloves, protective clothing, eye protection and face mask.

P370+P378 In case of fire: Use extinguishing powder, alcohol-resistant foam or carbon dioxide to

extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of container to waste disposal

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No.	Chemical Name	Chemical Name			Quantity
	EC No.	Index No.	REACH	No.	
	Classification according	Classification according to Regulation (EC) No. 1272/2008 (CLP)			
63148-62-9	Polydimethylsiloxane	Polydimethylsiloxane			50-70%
	613-156-5	Not applicable	Not applicable Not applicable		
	Not applicable				
25265-71-8	Dipropylene glycol	Dipropylene glycol			30-60%
	246-770-3	Not applicable	01-211	9456811-38-0000	
	Not applicable				
507-55-1	Fluorine Compound	Fluorine Compound			0.1-1%
	Not applicable	Not applicable	Not ap	plicable	
	STOT RE 2: H373				
5593-70-4	Titanium tetrabutanola	Titanium tetrabutanolate			0.1-1%
	227-006-8	Not applicable	01-211	9967423-33-0000	
	Flam. Liq 3: H226; Skin Irr. 2: H315; Eye Dam. 1: H318; STOT SE 3: H335				

#### 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

# **IGL COATINGS™ ECOCOAT KENZO K1 TOP**

Material no.

Specification 154344 Revision date 05.09.2022

Version **1.00** Page 2 of 6



#### **General Information**

Take persons to a safe place. Observe self-protection for first aid.

#### **After Inhalation**

Keep the patient calm. If unconscious place in stable sideways position.

#### After skin contact

Remove contaminated or soaked clothing. Wash off immediately with soap and plenty of water.

In event of a visible skin change or other complaints, seek medical advice.

#### After contact with eyes

Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses, if presence and easy to do. Seek medical advice in case of continuous irritation.

# **After ingestion**

Wash out mouth with water provided the person is conscious. Do not induce vomiting.

Seek medical advice immediately and clearly identify substance.

# 4.2. Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

# 4.3. Indication of any immediate medical attention and special treatment needed

In case of contact with water, material splits off methanol in larger amounts; therefore consider poisoning on methanol and also observe known period of latency of several days.

# 5. FIRE-FIGHTING MEASURES

# 5.1 Suitable extinguishing media

Water mist, extinguishing powder, alcohol resistant foam, carbon dioxide, sand.

# 5.2 Unsuitable extinguishing media

Water spray, water jet.

# 5.3 Special hazards arising from the substance or mixture

No information available.

# **5.4 Advise for firefighters**

Use respiratory protection independent of recirculated air.

# 5.5 Unusual Fire Hazards:

None.

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (Refer to section 8).

Keep unprotected persons away. Avoid contact with eyes and skin.

Avoid inhaling mists and vapours. If material is released, indicate risk of slipping.

# **6.2 Environmental precautions**

Prevent material from entering surface water, drains or sewers and soil.

Contain any fluid that runs out using suitable material (e.g. earth).

Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers.

# 6.3 Methods and material for containment and cleaning up

Do not flush away with water.

For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose according to local regulations. Clean any slippery coating that remains using a detergent/soap solution.

Exhaust vapour.

# 6.4 Reference to other sections

Safe handling: Refer to section 7

Personal protection equipment: Refer to section 8

Disposal: Refer to section 13

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

# **IGL COATINGS™ ECOCOAT KENZO K1 TOP**

Material no.

Specification 154344 Revision date 05.09.2022

Version **1.00** Page 3 of 6



#### Advice on safe handling

Wear personal protection equipment (Refer to section 8).

Ensure adequate ventilation.

Keep away from incompatible substances in accordance with section 10.

Spilled substance increases risk of slipping.

# **Precautions against fire and explosion**

Product can separate into methanol. Flammable vapours may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

# 7.2 Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Make sure there is no possibility of entering the ground.

# Advice on storage compatibility

Do not store together with food and feeding stuffs.

# **Further information on storage conditions**

Keep the packing dry and well-sealed to prevent contamination.

Recommended storage temperature: 20-25 °C.

Protect against: Moisture

**7.3. Specific end use(s):** Refer to section 1.

#### 8. EXPOSURE CONTROL/PERSONAL PROTECTION

#### 8.1 Control parameters

# Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional Information: The lists valid during the making were used as basis.

# **8.2 Exposure Control**

#### 8.2.1 General protective and hygienic measures:

Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols.

Do not eat, drink or smoke when handling.

# 8.2.2 Personal protective equipment:

#### **Respiratory protection:**

In case of long and strong exposure, use respirator with an ABEK filter.

# **Protection of hands:**

Use protective gloves made of butyl rubber. Gloves suitable for up to 60 minutes' use. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

# Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

# Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tight fitting protective goggles.

**Skin protection:** Protective clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point : 180-220 °C

Density :  $0.988 \text{ g/cm}^3 \text{ (at } 25 \text{ °C)}$ 

Flash Point : 70 °C

# **IGL COATINGS™ ECOCOAT KENZO K1 TOP**

Material no.

Specification 154344 Revision date 05.09.2022 Version

4 of 6 1.00 Page

рН : Not applicable Solubility in Water : Virtually insoluble

Appearance (colour) : Clear Appearance (form) : Liquid Odour : Peculiar

#### 10. STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

**10.2 Chemical stability**: Stable under normal condition.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions: No data available.
- **10.4 Conditions to avoid**: Moisture, heat, open flames and other sources of ignition.
- **10.5 Incompatible materials**: Oxidising agent, acids, water.
- 10.6 Hazardous decomposition products: When heated to temperatures above 150°C (300 F) in the presence of air, product can form formaldehyde vapours. Hazardous decomposition products will be formed upon contact with water or humid air.

#### 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects: No data available.

Skin corrosion/irritation: No data available.

Serious eye damage/eye irritation: No data available. Respiratory or skin sensitization: No data available.

Summary of evaluation of the CMR properties: No data available. Specific target organ toxicity - single exposure: No data available. Specific target organ toxicity - repeated exposure: No data available.

Aspiration hazard: No data available.

# 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No data available.

#### 12.2 Process of degradability

No data available.

# 12.3 Bioaccumulative potential

No data available.

#### 12.4 Mobility in soil

No data available.

# 12.5 Results of PBT and vPvB Assessment

No data available.

#### 12.6 Other adverse effects

No data available.

# 13. DISPOSAL CONSIDERATION

#### 13.1 Waste treatment methods

Recommendation: Dispose of according to regulations by incineration in a special waste incinerator.

Observe local/state/federal regulations.

# **Uncleaned packaging:**

Recommendation: Completely discharged containers (no tear drops, no powder rest, scraped carefully).

Containers may be recycled or reused. Observe local/state/federal regulations.

# Sewage disposal-related information

Do not empty into drains.

# 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to



# **IGL COATINGS™ ECOCOAT KENZO K1 TOP**

Material no.

Specification 154344 Revision date 05.09.2022

Version **1.00** Page 5 of 6



the industry and process.

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

#### 14. TRANSPORT INFORMATION

#### 14.1 IATA-DGR

UN number : -

UN proper shipping name : Non dangerous goods

Transport hazard class(es) : Packing group : Environmental hazards : No

Special precautions for user : No data available.

Remarks : -

14.2 IMDG-Code

UN number : -

UN proper shipping name : Non dangerous goods

Transport hazard class(es) : Packing group : Environmental hazards : No
Marine pollutant : No
EmS Code : -

# 15. REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

# **US. Toxic Substances Control Act (TSCA)**

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

# Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

None present or none present in regulated quantities.

# **Superfund Amendments and Reauthorization Act of 1986 (SARA)**

# **Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

# **Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting**

None present or none present in regulated quantities.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

# **US. State Regulation**

# **US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

#### **EU Regulation**

# EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

# IGL COATINGS™ ECOCOAT KENZO K1 TOP

Material no.

Specification 154344 Revision date 05.09.2022

Version **1.00** Page 6 of 6



# 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **16. OTHER INFORMATION**

# **Further information**

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.