


With a selection of reflectors, and four sizes (10W, 15W, 30W, 45W) from which to choose, the Ceti range of downlights are an excellent solution for your general lighting requirements. High-quality SMD LED chips provide accurate colour rendering and colour consistency, while ensuring long luminaire life.



Luminous Intensity Distribution Diagram (cd)



CETI 3 Interior | Recessed Downlight

Mechanical

Installation	Recessed
Housing Material	Die Cast Aluminium
Lens Material	Acrylic
Ingress Protection	IP44
Luminaire Diameter	Ø170mm
Luminaire Depth	85mm
Cut-out Diameter	Ø160mm
Weight	0.64 kg

Electrical

Luminaire Power	30W
Driver Included	Yes
Voltage Input	220-240V 50/60Hz AC
Drive Current	700mA

Light Source

LED	Everlight SMD2835
Beam Angle	90°
Luminaire Lumens	2,427lm
Colour Rendering (CRI)	Ra 90
Colour Consistency	SDCM 3
Lumen Maintenance	L70 40,000 hours



Ordering Information

Code		CETI 2	ССТ	Reflector	Co	olour I	Dimming
Example	(CI-3029	-W30	-MS		-W	-T
ССТ	Code	Reflector	Code	Colour	Code	Dimming	Code
2700K	W27	Matt Silver	MS	White	W	Trailing Edg	ge T
3000K	W30	Bright Silver	PS	Black	В	1-10V	А
4000K	W40	Bright Black	BB	Custom	С	DALI	D

P.O Box 673, Hamilton 3240, New Zealand | 07 856 3199 | info@impressionslighting.co.nz | www.impressionslighting.co.nz