


With a selection of reflectors, and four sizes (10W, 15W, 30W, 45W) from which to choose, the Ceti range of downlights are an excellent solution for your general lighting requirements. High-quality SMD LED chips provide accurate colour rendering and colour consistency, while ensuring long luminaire life.



Luminous Intensity Distribution Diagram (cd)



Mechanical


Installation	Recessed
Housing Material	Die Cast Aluminium
Lens Material	Acrylic
Ingress Protection	IP44
Luminaire Diameter	Ø230mm
Luminaire Depth	100mm
Cut-out Diameter	Ø215mm
Weight	1.01 kg

Electrical

Luminaire Power	45W
Driver Included	Yes
Voltage Input	220-240V 50/60Hz AC
Drive Current	1050mA

Light Source

LED	Everlight SMD2835
Beam Angle	90°
Luminaire Lumens	3,875lm
Colour Rendering (CRI)	Ra 90
Colour Consistency	SDCM 3
Lumen Maintenance	L70 40,000 hours



Ordering Information

Code	CETI 2	CCT	Reflector	Colour	Dimming		
Example	CI-3030	-W30	-MS	-W	-T		
CCT	Code	Reflector	Code	Colour	Code	Dimming	Code
2700K	W27	Matt Silver	MS	White	W	Trailing Edge	T
3000K	W30	Bright Silver	PS	Black	B	1-10V	A
4000K	W40	Bright Black	BB	Custom	C	DALI	D

