


Available in a range of sizes and wattages, and with dimming options, the Electra is a versatile downlight suitable for many general lighting requirements. Powder coated, high grade die -cast aluminium housing for an aesthetically pleasing look, with high-quality LED technology for colour quality characteristics which subtly complement, and enhance the space.



Luminous Intensity Distribution Diagram (cd)



ELECTRA 2

Mechanical


Installation	Recessed
Housing Material	Die Cast Aluminium
Lens Material	Acrylic
Ingress Protection	IP44
Luminaire Diameter	115mm
Luminaire Depth	60mm
Cut-out Diameter	100mm
Weight	0.43 kg

Electrical

Luminaire Power	15W
Driver Included	Yes
Voltage Input	220-240V AC
Drive Current	350mA

Light Source

LED Manufacturer	Everlight SMD
LED Series	SMD2835
Beam Angle	90°
Luminaire Lumens	820lm
Colour Rendering (CRI)	Ra 90
Colour Consistency	SDCM 3
Lumen Maintenance	L70 40,000 hours



100

Ordering Information

Code	EL	ECTRA 2	ССТ	Wattag	e C	Colour	Dimming	
Example EA-3004		EA-3004	-W30	-15 -W		-W	-T	
ССТ	Code	Wattage	Code	Colour	Code	Dimming	Code	
2700K	W27	15W	15	White	W	Trailing Ed	ge T	
3000K	W30			Black	В	1-10V	А	
4000K	W40			Custom	С	DALI	D	

P.O Box 673, Hamilton 3240, New Zealand | 07 856 3199 | info@impressionslighting.co.nz | www.impressionslighting.co.nz