


Available in a range of sizes and wattages, and with dimming options, the Electra is a versatile downlight suitable for many general lighting requirements. Powder coated, high grade die -cast aluminium housing for an aesthetically pleasing look, with high-quality LED technology for colour quality characteristics which subtly complement, and enhance the space.



Luminous Intensity Distribution Diagram (cd)



ELECTRA 3

Mechanical


| Installation | Recessed |
|--------------------|--------------------|
| Housing Material | Die Cast Aluminium |
| Lens Material | Acrylic |
| Ingress Protection | IP44 |
| Luminaire Diameter | 160mm |
| Luminaire Depth | 60mm |
| Cut-out Diameter | 150mm |
| Weight | 0.81 kg |

Electrical

| Luminaire Power | 15W 25W |
|-----------------|---------------|
| Driver Included | Yes |
| Voltage Input | 220-240V AC |
| Drive Current | 350mA 600mA |

Light Source

| LED Manufacturer | Everlight SMD |
|------------------------|-------------------|
| LED Series | SMD2835 |
| Beam Angle | 100° |
| Luminaire Lumens | 1,200lm 1,869lm |
| Colour Rendering (CRI) | Ra 90 |
| Colour Consistency | SDCM 3 |
| Lumen Maintenance | L70 40,000 hours |



Ordering Information

| Code | EL | ECTRA 3 | ССТ | Wattag | e C | Colour | Dimming |
|---------|------|---------|------|--------|------|-------------|---------|
| Example | E | EA-3006 | -W30 | -15 | | -W | -T |
| ССТ | Code | Wattage | Code | Colour | Code | Dimming | Cod |
| 2700K | W27 | 15W | 15 | White | W | Trailing Ec | lge T |
| 3000K | W30 | 25W | 25 | Black | В | 1-10V | А |
| 4000K | W40 | | | Custom | С | DALI | D |

P.O Box 673, Hamilton 3240, New Zealand | 07 856 3199 | info@impressionslighting.co.nz | www.impressionslighting.co.nz