S75/C68

The grinder reinvented

ADVERTISING DISPLAY

Improve customer engagement while maintaining hopper appearance hygienic and clean

SIDE PANELS

Removable for easy access and customization

MODULAR DESIGN

For speed of service and reduced downtime

FRESHNESS METER

Coffee quality control to guarantee the best extraction

DETACHABLE POWER CORD

Easy to remove from the workbench



MIXING CHAMBER

Steady coffee extraction thanks to uniform grinding and dose

MICROMETRIC GRINDING ADJUSTMENT

Fast and accurate stepless grind setting, easy to adjust and communicate/verify

DELIVERY SPEED

Faster than an instant grinder

ADJUSTABLE SLIDE

Allows to use most of the portafilters on the market

SERVICE MODE KNOB

2 in 1 grinder to choose immediately the grinding between auto/semi-auto mode

S75/C68

The grinder reinvented

TECHNOLOGIES



Delivery system

No more coffee waste for a more sustainable money savvy grinder and a clean work area



Belt driven motor

No heat transfer from motor, lower temperature fluctuation for ground coffee, steadier extraction



Conical/flat burrs

Pick the suitable burrs to optimize the sensory profile according to your coffee of choice (single origin or blend)



Cylinder/burrs adjustment

Easy burr alignment with memory of setting (both conical/flat), reduces service time and cost

TECHNICAL DATA

| | S75 | C68 |
|-----------------------|----------------------|----------------------|
| Dimensions (WxHxD) | 212x632x440 mm | 212x632x440 mm |
| Weight | 24 kg | 24 kg |
| Burrs type/size | Flat 75 mm | Conical 68 mm |
| Voltage | 220 - 240 V 50/60 Hz | 220 - 240 V 50/60 Hz |
| Watts | 450/570 W | 450/570 W |
| Motor speed | 1215 - 1458 rpm | 450 - 540 rpm |
| Noise level | 87 Dba | 87 Dba |
| Hopper capacity | 1,2 kg | 1,2 kg |