


# Right Angle QMA-Male to N-Female Pigtail Adapter

by WAVEFORM

SKU: PTA-RAQMAM-NF

## Main Features:

- Right Angle QMA-Male to N-Female adapter
- 0-6000 MHz
- 50  $\Omega$
- 4.95 mm diam. cabling



Section Description	Material	Plating
QMA Body	Brass	Nickel
N Body	Brass	Nickel
Crimping Suite	Copper Alloy	Nickel
Outer Conductor	Copper	Silver
Inner Conductor	Copper Clad Steel	Silver
Jacket	FEP	
Gasket	Silicone Rubber	
Dielectric	PTFE	

## Specifications:

Electrical:		Mechanical:		Environmental:	
Input Impedance	50 $\Omega$	Jacket Color	Tan	Burial Rated?	No
Frequency Range	0 - 6000 MHz	Cable Type	RG142	UV Rated?	No
VSWR	$\leq 1.2$	Cable Diameter	4.95 mm	Operating Temperature	-65 to +165 deg C
Capacitance	< 29.4 pF/m	Cable Length	20 cm		
Velocity	70 %	Bending Radius	25.4 mm		
Shielding	> 88 dB	Connector A Type	QMA-Male		
Power Rating (Peak)	5 kW	Connector A Angle	Right		
Insertion Loss (Typical)	< 0.7 dB @ 6000 MHz	Connector A Diameter	10.4 mm		
		Connector B Type	N-Female		
		Connector B Angle	Straight		
		Connector B Diameter	15.7 mm		
		Net Weight	32 g		



WAVEFORM

3411 W. Lake Center Drive,  
Santa Ana, CA 92704

www.waveform.com  
1-800-761-3041