

SMA-Male to N-Male Pigtail Adapter


by WAVEFORM

SKU: PTA-SMAM-NM



Main Features:

- SMA-Male to N-Male connector
- 0-6000 MHz
- 50 Ω
- 4.95 mm diam. cabling



Section Description	Material	Plating
SMA Body	Brass	Gold/Nickel
N Body	Brass	Gold/Nickel
Crimping Suite	Copper Alloy	Nickel
Inner Conductor	Brass	Gold/Silver
Jacket	FEP	
Gasket	Silicone Rubber	
Dielectric	PTFE	

Specifications:

Electrical:		Mechanical:		Environmental:	
Input Impedance	50 Ω	Jacket Color	Tan	Burial Rated?	No
Frequency Range	600 - 6000 MHz	Cable Type	RG142	UV Rated?	No
VSWR	≤ 1.2	Cable Diameter	4.95 mm	Operating Temperature	-65 to +165 deg C
Capacitance	< 29.4 pF/m	Cable Length	15 cm		
Velocity	70 %	Bending Radius	25.4 mm		
Shielding	> 88 dB	Connector A Type	SMA-Male		
Power Rating (Peak)	5 kW	Connector A Angle	Straight		
Insertion Loss (Typical)	< 0.7 dB @ 6000 MHz	Connector A Diameter	7.9 mm		
		Connector B Type	N-Male		
		Connector B Angle	Straight		
		Connector B Diameter	20.3 mm		
		Net Weight	34 g		



WAVEFORM

3411 W. Lake Center Drive,
Santa Ana, CA 92704

www.waveform.com
1-800-761-3041