



## Home/Commercial Booster HiBoost Elite PRO 4G LTE F20G-5S

### Overview

HiBoost Elite PRO 4G LTE (F20G-5S) is a wide band booster that amplifies signals of all operators in the mobile system and supports 2G, 3G and 4G voice that covers up to 7,500 square feet. With the capacity to support 200 cell phone and device users, everyone can enjoy the freedom of clear calls and constant high speed data.



### FCC fulfillment

- FCC Grant Code OWW for this series product. To get detail information, go to <https://apps.fcc.gov/oetcf/eas/reports/GenericSearch.cfm>
- FCC approved this equipment for use with all US carriers
- The FCC ID for this equipment is OWWF20G-CPAL-AB-C



### Key Features

- Supports up to 200 users
- Covers up to 7500 square feet
- All 2G, 3G and 4G standards are supported
- Low interference to cell tower
- FCC certified
- MGC function special for electric fans
- Streamline design
- Quality metal construction, strong and durable



### Booster Kit Includes

- Elite PRO 4G LTE 70dB cell phone booster
- Outdoor Logarithmic periodic antenna with 50 feet 5D-FB cable
- Indoor panel antenna with 15 feet 5D-FB cable

Address: 6210 N. Belt Line Road, Suite 110, Irving, TX 75063 Phone: (972)870-5666 E-mail: [info@huaptecus.com](mailto:info@huaptecus.com)  
Website: [www.huaptecus.com](http://www.huaptecus.com)

## Specification

Electrical specification	
UL Frequency Range	698-716 / 776 – 787 / 824-849 / 1850-1910 / 1710-1755
DL Frequency Range	728-746 / 746 – 757 / 869-894 / 1930-1990 / 2110-2155
Supported Standards	CDMA, WCDMA, GSM, EDGE, HSPA+, EVDO, LTE and all cellular standards
Max .Gain	70dB
MGC ( Step Attenuation )	31dB/1dB step
Automatic Gain Control	31dB
I/O Port	N-Female
Impedance	50 ohm
Environment Conditions	IP40
Dimensions	8.6*6.5*2inch/218*165*50mm
Weight	≤5.5Lbs/2.5Kg
Power Supply	Input AC100~240V,50/60Hz,Output DC12V / 3A

## Installation Example

