

AT-XC SHORT ACTION 6.5 CREEDMOOR /.308 WIN COMPETITION RIFLE

The next generation Accuracy International high performance, low profile AT-XC rifle features cross-platform enhancements to match the demands of sporting communities worldwide.

Victory in the balance

With a cut-rifled barrel manufactured by Al in the UK and central point of balance delivering linear recoil, no muzzle jump and rapid setup, the AT-XC is a rigid and reliable platform for accuracy at speed.

Al quality without compromise

The AT-XC Comp/Pro model comes complete with all the accessories configured for the perfect Factory Div rifle. Al accuracy, repeatability and reliability naturally come as standard.

Low profile, High performance

The non-bonded barrelled short action is bolted into a low profile chassis.

The slick action builds trust and confidence in its capabilities.



ACCURATE RUGGED RELIABLE



SHORT ACTION 6.5 CREEDMOOR /.308 WIN COMPETITION RIFLE

AT-XC STANDARD MODEL

Fixed stock with removeable interface for folding hinge accessory Long bridge available as factory option



CALIBRES	BARREL LENGTH	MUZZLE THREAD	MUZZLE BRAKE
6.5 Creedmoor	24" (610 mm)	5/8" x 24 UNEF	NONE
6.5 Creedmoor	26" (660 mm)	18 x 1.5 mm	Al tactical muzzle brake
.308 WIN	20" (508 mm)	5/8" x 24 UNEF	NONE
.308 WIN	20" (508 mm)	18 x 1.5 mm	Al tactical muzzle brake
.308 WIN	24" (610 mm)	5/8" x 24 UNEF	NONE
.308 WIN	24" (610 mm)	18 x 1.5 mm	Al tactical muzzle brake
.308 WIN	26" (660 mm)	5/8" x 24 UNEF	NONE
.308 WIN	26" (660 mm)	18 x 1.5 mm	Al tactical muzzle brake

AT-XC COMP/PRO MODEL

Includes long bridge, folding hinge, rear grip and external weights



CALIBRES	BARREL LENGTH	MUZZLE THREAD	MUZZLE BRAKE
6.5 Creedmoor	24" (610 mm)	5/8" x 24 UNEF	NONE
6.5 Creedmoor	26" (660 mm)	18 x 1.5 mm	Al tactical muzzle brake
.308 WIN	24" (610 mm)	5/8" x 24 UNEF	NONE
.308 WIN	26" (660 mm)	18 x 1.5 mm	Al tactical muzzle brak

GENERAL SPECIFICATION

Trigger: Choice of the Al standard trigger or XTSP Al competition trigger

Action: Next generation action with enhanced features, 3 position safety catch on the bolt shroud, 6 lug 60° dynamic bolt lift and enlarged bolt handle

Chassis: 7075 aluminium chassis with superior AI KeySlot™ mounting system, featuring 20 MOA Action Rail, and AI repeatable Quickloc barrel change system

Toolless quick adjustable cheekpiece: Height range: 24.5mm (0.96") in 3.5mm (0.14") increments

Target adjustable buttpad and length of pull: Min 321mm (12.6") with a total range of 55mm (2.15")

Min 321mm (12.6") with a total range of 55mm (2.15" in 5.5mm (0.215") increments. Additional accessory butt spacers (standard or weighted) also available

Forend: Low profile single plane forend 397mm (15.63") to fit barrels with a minimum length of 508mm (20") and maximum diameter of 31mm (1.22"). Integral RRS spec rail interface Length: 445mm (17.5"), KeySlot™ mounting system and machined barrier support

Magazine: Slim profile mag catch for ambidextrous removal. 1 x detachable 10 round double stack magazine

Al barrel options: Al profile and cut-rifled competition grade barrels manufactured in England by Al UK

Grip: Designed to accept most AR style pistol grips

Sling attachment points

User manual

Colours: The AT-XC chassis is protected with a Cerakote™ top coat available in four colours



Accuracy International Ltd

Portsmouth, UK T: +44 (0)23 9267 1225 E: ai@accuracyinternational.org W: www. accuracyinternational.com







