SHORT ACTION 6.5 CREEDMOOR COMPETITION RIFLE



CALIBRE

6.5 Creedmoor (short action)

WEIGHT

With magazine, no scope and 24" barrel: 5.94 kg (13.1 lbs)

LENGTH

With butt pad not extended and 24" barrel: 1086 mm (42.75 ins)



Accuracy International Ltd

Portsmouth, UK T: +44 (0)23 9267 1225 E: ai@accuracyinternational.org www. accuracyinternational.com

BASE RIFLE

Chassis

7075 billet aluminium chassis, fixed butt stock. Removable interface for folding hinge accessory

Toolless quick adjust target butt pad

Adjustable length of pull: min. 321 mm (12.6") with a total range of 55 mm (2.15") in 5.5 mm (0.215") increments. Additional butt spacers (standard or weighted) can also be used

Toolless quick adjust cheekpiece

Height adjustable range: 22 mm (0.86") in 5.5 mm (0.215") increments

Pistol grip

Designed to accept most AR style pistol grips

Action

Standard AT/AX short action with 20MOA low action rail, bolted to the chassis

Quickloc

Al patented barrel removal/change system

Bolt

6 lug, 60° bolt lift with leaf spring extractor and 1.6mm firing pin

Safety

Three position safety on bolt shroud

Trigger: AI USA / XTSP heavy spring competition trigger. Adjustable pull weight: 0.68 - 1.25 kg (1.5 - 2.75 lb)

Magazine

1 x detachable 10-round double stack magazine - can also be top loaded though the rifle ejection port. Left side magazine port cut out for ease of magazine insertion plus new slim profile mag catch for ambidextrous extraction

Forend

Low profle single plane forend with integral RRS spec. rail interface, KeySlot™ mounting system and machined barrier support Length: 445 mm (17.5")

Sling attachment points

KeySlot™ mounting system

Featured on the forend and right hand side of the magazine aperture, Al's patented KeySlot™ mounting system allows rapid and secure attachment of rails or other accessories

User manual

OPTIONS / ACCESSORIES

Al barrel options

416 stainless steel, 6 groove 'competition' grade heavy profile cut-rifled barrels manufactured in England by AI UK

24" (610 mm) with $5/8 \times 24$ UNEF threaded muzzle with thread protector*

26" (660 mm) with 18×1.5 mm metric threaded muzzle with thread protector for Al muzzle brake*

* Base rifle does not include muzzle brake

Short and long forend bridges

Easily attached to the forend interface, a bridge adds extra space for KeySlot™ rails and accessories whilst protecting the barrel

Short Bridge incl. 4 screws 19 cm (approx. 7.5")

Long Bridge** incl. 6 screws 40 cm (approx. 15.5")

**Also deliverable as a factory fitted option

KeySlot[™] forend weights

Internal/external/stackable weights reduce recoil and increase stability. Supplied individually with 2 reverse CSK screws installed (spares available)

External/stackable weights (black)

Stacking increases weight and width for added stability on a bag

Heavy approx. 8 oz (227 g) Light approx. 6 oz (170 g)

Stacking fasteners individual or pack of 12

Internal weight (black) approx. 6 oz (170 g)
Attachable along the internal

floor of the forend Butt spacer weights

Extend LOP whilst enhancing weight, stability and balance



600 · 00

Folding stock hinge

Replaces fixed interface to create a folding stock

Al muzzle brake | Rear grip





