

LONG ACTION MULTI CAL RIFLE

The next generation Accuracy International high performance, AXSR rifle features cross-platform enhancements to match the demands of sporting communities worldwide.

Victory in the balance

With a cut-rifled barrel manufactured by Al in the UK and central point of balance delivering linear recoil, no muzzle jump and rapid setup, the AXSR is a rigid and reliable platform for accuracy at speed.

Al quality without compromise

The AXSR model comes complete with all the options configured for the perfect rifle. Al accuracy, repeatability and reliability naturally come as standard.

Reliable high performance

The non-bonded barrelled long action is bolted into an aluminium chassis. With RRS spec (ARCA Swiss compatible) rail interface forend for tripod mounting. The slick action builds trust and confidence in its capabilities.



ACCURATE RUGGED RELIABLE



LONG ACTION MULTI CAL RIFLE









CALIBRES	BARREL LENGTH	MUZZLE THREAD	MUZZLE BRAKE	MOUNTING SYSTEM	TWIST RATE
6.5 Creedmoor	24" / 26" (610mm / 660mm)	3/4" × 24BN	B&T AI SPEC	KeySlot™	1:8
.308 WIN	26" (660mm)	3/4" x 24BN	B&T AI SPEC	KeySlot™	1:10
.300 WIN MAG	26" (660mm)	3/4" x 24BN	B&T AI SPEC	KeySlot™	1:11
.338 LAPUA MAG	27" (686mm)	3/4" x 24BN	B&T AI SPEC	KeySlot™	1:9.35



Accuracy International Ltd Portsmouth, UK T: +44 (0)23 9267 1225

E: ai@accuracyinternational.org W: www. accuracyinternational.com

©Accuracy International 2024. Issue: 01. All rights reserved. Specification may be subject to change without notice

GENERAL SPECIFICATION

Trigger: Al standard two-stage trigger adjustable weight between 1.5 and 2Kg

Action: Proofed EN24T steel action and bolt body with maraging steel bolt head and lock ring 6 lug 60° dynamic bolt lift. Action rail and forend rail 30 MOA STANAG 4694 / Mil Std for use with in-line night vision or thermal scopes. Action bolted to the aluminium chassis with 5 action screws

Safety catch: Ambidextrous 2 position safety catch

Chassis: 7075 aluminium chassis with superior AI KeySlot™ mounting system, featuring 30 MOA Action Rail, and AI repeatable Quickloc barrel change system

Toolless quick adjustable cheekpiece: Height range: 22mm (0.86") in 3.2mm (0.12") increments

Target adjustable buttpad and length of pull: Min 321mm (12.6") with a total range of 55mm (2.15") in 3.2mm (0.12") increments

Forend: Integral RRS spec rail interface, KeySlot[™] mounting system and machined barrier support

Magazine: Slim profile mag catch for ambidextrous removal. 1 x detachable 10 round double stack magazine

Al barrel options: Cut heavy profile with M30 barrel tenon, manufactured in England by Al UK

Grip: Designed to accept most AR style pistol grips

Folding stock: Right side folding stock over bolt for shorter profile during transportation

Suppressor: B&T AG muzzle brake designed for use with B&T AG suppressor

Sling attachment points

User manual

Colours: The AXSR is protected with a Cerakote[™] top coat available in three colours

