

# AT-X

SHORT ACTION 6.5 CREEDMOOR COMPETITION RIFLE



**The Accuracy International AT-X rifle has been specifically designed and engineered to match the rigorous demands of the growing civilian competition shooting community worldwide.**

#### **Low profile, high performance**

The non-bonded standard (AT/AX) barrelled short action is bolted into a sleek low profile chassis to minimise height over bore, enhancing barricade support and porthole clearance during competitions.

#### **Victory in the balance**

With a cut-rifled competition barrel manufactured by AI in the UK and central fulcrum of balance delivering linear recoil, no muzzle jump and rapid setup, the AT-X is a sure-fire winner.

#### **AI quality without compromise**

Using optional accessories a base AT-X rifle can swiftly be configured to create a perfect fit for every shooter. AI accuracy, repeatability and reliability naturally come as standard.

ACCURATE / RUGGED / RELIABLE





# AT-X

## SHORT ACTION 6.5 CREEDMOOR COMPETITION RIFLE



### COLOURS

The AT-X chassis is protected with a base anodize hard coat and a Cerakote™ top coat in the following colours:

BLACK

DARK EARTH

ELITE SAND

RED

BLUE

### CALIBRE

6.5 Creedmoor (short action)

### WEIGHT

With magazine, no scope and 24" barrel:  
5.94 kg (13.1 lbs)

### LENGTH

With butt pad not extended and 24" barrel:  
1086 mm (42.75 ins)

### BASE RIFLE

#### Chassis

7075 billet aluminium chassis, fixed butt stock. Removable interface for folding hinge kit available as accessory

#### Target adjustable butt pad

Adjustable length of pull: min. 321 mm (12.6") with a total range of 55 mm (2.15") in 5.5 mm (0.215") increments. Additional butt spacers can also be used

#### Rear grip

Fitted to a picatinny rail with one screw for ease of placement or removal

#### Cheekpiece

Height adjustable range: 22 mm (0.86") in 5.5 mm (0.215") increments

#### Pistol grip

Designed to accept most AR style pistol grip

#### Action

Standard AT/AX short action with 20MOA low action rail, bolted to the chassis

#### Quickloc

AI patented barrel removal/change system

#### Bolt

6 lug, 60° bolt lift with leaf spring extractor and 1.6mm firing pin

#### Safety

Three position safety on bolt shroud

#### Trigger

AI USA / XTSP competition trigger. Adjustable pull weight: 0.68 - 1.25 kg (1.5 - 2.75 lb) heavy spring

#### Magazine

1 x detachable 10-round double stack magazine P/N AI-6677 - can also be top loaded though the rifle ejection port. Left side magazine port cut out for ease of magazine insertion plus new slim profile mag catch for ambidextrous extraction

#### Forend

Low profile single plane forend with integral RRS spec. rail interface, KeySlot™ mounting system and machined barrier support Length: 445 mm (17.5")

### KeySlot™ mounting system

Featured on the forend and right hand side of the magazine aperture, AI's patented KeySlot™ mounting system allows rapid and secure attachment of rails or other accessories

### Barrel

416 stainless steel, 6 groove, 1:8 twist 24" (610 mm) 6.5 Creedmoor, 'competition' grade heavy profile cut-rifled barrel with 5/8 x 24 UNEF threaded muzzle with thread protector included. Manufactured in England by AI UK (base rifle does not include muzzle brake)

### Sling attachment points

### User manual

### ACCESSORIES



#### Short and long forend bridges

Easily attached to the forend interface, a bridge adds extra space for KeySlot™ rails and accessories whilst protecting the barrel

#### Folding stock hinge

Replaces interface to create a folding stock

#### Weights

Internal, external and stackable .227 kg (½ lb) weights to reduce recoil and increase width for increased contact / stability on a bag

### Accuracy International Ltd

Portsmouth, UK

T: +44 (0)23 9267 1225

E: ai@accuracyinternational.org

W: www.accuracyinternational.com

©Accuracy International 2021. Issue: 01. All rights reserved  
Specification may be subject to change without notice

