

# Installation of the Integrated Mount Universal Night Sight (IMUNS)

For all Accuracy International AW Rifles and AICS Chassis Systems

## Read these instructions completely before beginning!

\* This work must be performed by an Armourer familiar with these types of rifles.\*

\* Per owners/Operators manual remove side panels (Skins). Use a 2.5mm hex wrench. \*

1. Using a 5/16" pin punch, remove the 8mm roll pin (10)
2. Slide the bipod mounting block forward until the Sling Mounting plate (9) can be removed left to right, pull the bipod mounting block the rest of the way out. Remove the bipod latch, spring and pin (11, 12, 13) if you intend to install it in the IMUNS.
3. If you intend to install the bipod latch, do this now.
4. Slip the Bipod Mounting Block (2) into the Chassis tube and install the Sling mounting plate (9)
5. Tighten grub screw (6) to prevent sling mounting plate rattle.
6. Line up the hole for the 8mm roll pin and install it (10). Install the Lock plate (3) with Screws (8) onto the bottom of the chassis tube, using M5 hex wrench, tighten finger tight and add approx. 120° of torque or use a 65 In-Lbs wrench.
7. Re-install the side panels (Skins) per owners/Operators manual.
8. The top of the IMUNS (1) can removed with a T-15 Torx wrench for installation of the barreled action (AICS ) or to extend the rail to the front or rear, re-install Screws (7) finger tight plus 90°.
9. The Side rail (4) and its screws (5) may also be installed to fit your specific requirement

Name	PIN	Qty
Rail, IMUNS Reversible Top	1	1 Ea.
IMUNS, Bottom/Bipod Mounting Block	2	1 Ea.
Plate, Lock	3	1 Ea.
Rail, Side	4	1 Ea.
Screw, Cap Head M4	5	2 Ea.
Grub Screw, nylon tip, M5	6	1 Ea.
Screw, Cap Head Torx T15	7	6 Ea.
Screw ¼ x 20UNC x 9/16"	8	2 Ea.
Plate sling mounting	9	1 Ea.
Pin, Roll 8mm	10	1 Ea.
Pin roll 3mm, bipod latch	11	1 Ea.
Latch Bipod	12	1 Ea.
Spring Bipod latch	13	1 Ea.