

LCexv 4010



MediLine



Gross/net capacity	361/345 litre
Ext. dimensions in mm (w/d/h)	597/615/2003
Int. dimensions in mm (w/d/h)	440/441/1105
Energy consumption in 365 days	657 kWh
Climate rating	7 ¹
Refrigerant	R 600a
Airborne acoustical noise emissions	52 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	forced-air/static
Defrosting	automatic/manual
Temperature range	+3°C to +16°C / -9°C to -30°C
Gradient *	
fridge/freezer comp.	4.0°C / 7.9°C
Max. fluctuation **	
fridge/freezer comp.	3.9°C / 5.5°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Number of drawers	3
Adjustable Shelving	4
Shelf material	glass/glass
Shelf loading	45 kg / 24 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	70 mm
Gross/net weight	93 / 87 kg
EAN-Nr.	9005382197172

1 Climate class / Climate Rätting: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C
3 +10°C to +25°C **4** +10°C to +30°C **5** +10°C to +40°C **7** +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.