LCv 4010

MediLine



Gross/net capacity	361/345 litre
Ext. dimensions in mm (w/d/h)	597/615/2003
Int. dimensions in mm (w/d/h)	440/441/1105
Energy consumption in 365 days	657 kWh
Climate rating	7 1
Refrigerant	R 600a
Airborne acoustical noise emissions	52 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	forced-air/static
Defrosting	automatic/manual
Temperature range	+3°C to +16°C / -9°C to -30°C
Gradient *	
fridge/freezer comp.	5.2°C / 7.9°C
Max. fluctuation **	
fridge/freezer comp.	5.7°C / 5.5°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Number of drawers	3
Adjustable Shelving	4
Shelf material	grid shelves plastic-coated/glass
Shelf loading	45 kg / 24 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation Cross/pat weight	70 mm
Gross/net weight EAN-Nr.	90 / 84 kg 9005382196977
EAIV-IVI.	9005362196977

1 Climate class / Climate $R\overline{a}$ ting: SN +10°C to +32°C

N +16°C to +32°C

ST +16°C to +38°C

T +16°C to +43°C

³ +10°C to +25°C

^{4 +10°}C to +30°C

⁵ +10°C to +40°C

^{7 +10°}C to +35°C

^{*} Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

*** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.