LGT 2325

LED

MediLine

Gross/net capacity	215/201 litre
Ext. dimensions in mm (w/d/h)	1138/740/915
Int. dimensions in mm (w/d/h)	889/410/630
Energy consumption in 365 days	824 kWh
Climate rating	4 [1]
Refrigerant	R 290
Airborne acoustical noise emissions	55 dB(A)
Connection Rating	2.0 A
Voltage	220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-10°C to -45°C
Gradient *	4.7°C
Max. fluctuation **	1.9°C
Lid material	Steel
Housing material/colour	steel/white
Liner Material	white-coated aluminium
Type of Control	electronic controller
Temperature display	external digital
Interface	RS 485
volt-free alarm contact	yes
Maximum number of baskets	10
Handle	aluminium shape
Lock	fitted
Insulation	120 mm
Defrost water drain	yes
Gross/net weight	68 / 58 kg
EAN-Nr.	9005382201114

Subject to modification. Timestamp: 13.12.2018

1 **Climate class** / Climate Rating:

SN +10°C to +32°C	**N** +16°C to +32°C	**ST** +16°C to +38°C	**T** +16°C to +43°C
3 +10°C to +25°C	**4** +10°C to +30°C	**5** +10°C to +40°C	**7** +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

LIEBHERR