## **LGT 3725**

## MediLine

Airborne acoustical noise emissions	55 dB(A)
Connection Rating	3.0 A
Voltage	220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-10°C to -45°C
Gradient *	4.3°C
Max. fluctuation **	2.2°C
Lid material	Steel
Housing material/colour	steel/white
Liner Material	white-coated aluminium
Type of Control	electronic controller
Temperature display	external digital
Interface	RS 485
volt-free alarm contact	yes
Maximum number of baskets	13
Handle	aluminium shape
Lock	fitted
Insulation	100 mm
Defrost water drain	yes
Gross/net weight	82 / 71 kg
EAN-Nr.	9005382168417

365/342 litre

1373/808/919

1170/500/650

1069 kWh

4 1

R 290



1 Climate class / Climate Rating: SN +10°C to +32°C

**3** +10°C to +25°C

**N** +16°C to +32°C 4 +10°C to +30°C **ST** +16°C to +38°C **5** +10°C to +40°C

Gross/net capacity

Climate rating

Refrigerant

Ext. dimensions in mm (w/d/h)

Int. dimensions in mm (w/d/h)

Energy consumption in 365 days

T +16°C to +43°C 7 +10°C to +35°C

\* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

\*\*\* Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.