## **LGUex 1500**

## MediLine



	****
Voltage	220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-9°C to -26°C
Gradient *	6.6°C
Max. fluctuation **	3.3°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Number of drawers	3
Number of baskets	1
Maximum number of baskets	4
Shelves	4
Shelf material	evaporator plates
Shelf loading	24 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	55 mm
Gross/net weight	45 / 42 kg
EAN-Nr.	9005382193198

139/129 litre

597/615/820

454/450/663

338 kWh

45 dB(A)

1.0 A

7 1 R 600a

Gross/net capacity

Climate rating

**Connection Rating** 

Refrigerant

Ext. dimensions in mm (w/d/h)

Int. dimensions in mm (w/d/h)

Energy consumption in 365 days

Airborne acoustical noise emissions



1 Climate class / Climate Rating: SN +10°C to +32°C **ST** +16°C to +38°C N +16°C to +32°C T +16°C to +43°C **3** +10°C to +25°C 4 +10°C to +30°C **5** +10°C to +40°C 7 +10°C to +35°C

\* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
\*\*\* Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.