LKUexv 1610

MediLine

Connection Rating	1.0 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+3°C to +16°C
Gradient *	3.9°C
Max. fluctuation **	4.8°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Adjustable Shelving	3
Shelf material	glass
Shelf loading	40 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	41 / 38 kg
EAN-Nr.	9005382197134

141/130 litre

597/615/820

440/435/670

315 kWh

47 dB(A)

5 1 R 600a



1 Climate class / Climate Rating: SN +10°C to +32°C

3 +10°C to +25°C

N +16°C to +32°C 4 +10°C to +30°C **ST** +16°C to +38°C **5** +10°C to +40°C

Gross/net capacity

Climate rating

Refrigerant

Ext. dimensions in mm (w/d/h)

Int. dimensions in mm (w/d/h)

Energy consumption in 365 days

Airborne acoustical noise emissions

T +16°C to +43°C 7 +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
*** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.