

# LKUv 1613

LED

## MediLine



Gross/net capacity	152/143 litre
Ext. dimensions in mm (w/d/h)	597/615/820
Int. dimensions in mm (w/d/h)	440/435/670
Energy consumption in 365 days	369 kWh
Climate rating	7 <sup>1</sup>
Refrigerant	R 600a
Airborne acoustical noise emissions	47 dB(A)
Connection Rating	1.0 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+3°C to +16°C
Gradient *	5.1°C
Max. fluctuation **	4.9°C
Housing material/colour	steel/white
Door/lid material	Insulated glazed door
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	external digital
Interior light	LED
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Adjustable Shelving	3
Shelf material	grid shelves plastic-coated
Shelf loading	45 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	46 / 43 kg
EAN-Nr.	9005382193235

1 Climate class / Climate Rätting: **SN** +10°C to +32°C    **N** +16°C to +32°C    **ST** +16°C to +38°C    **T** +16°C to +43°C  
**3** +10°C to +25°C    **4** +10°C to +30°C    **5** +10°C to +40°C    **7** +10°C to +35°C

\* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

\*\* Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.