LKexv 5400

MediLine





Gross/net capacity	554/520 litre
Ext. dimensions in mm (w/d/h)	750/730/1640
Int. dimensions in mm (w/d/h)	600/560/1452
Energy consumption in 365 days	359 kWh
Climate rating	5 ¹
Refrigerant	R 600a
Airborne acoustical noise emissions	48 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Gradient *	6.9°C
Max. fluctuation **	5.8°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	analgoue controls
Temperature display	external digital
Adjustable Shelving	5
Shelf material	glass
Shelf loading	40 kg
Handle	Ergonomic door handle
Lock	fitted
Door hinges	right, reversible
Gross/net weight	84 / 77 kg
EAN-Nr.	9005382164853

1 Climate class / Climate $R\overline{a}$ ting: SN +10°C to +32°C

N +16°C to +32°C 4 +10°C to +30°C

ST +16°C to +38°C

T +16°C to +43°C

³ +10°C to +25°C

⁵ +10°C to +40°C

^{7 +10°}C to +35°C

^{*} Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.