SUFsg 7001

MediLine

Gross/net capacity	728/700 litre
Ext. dimensions in mm (w/d/h)	1205/1085/1966
Int. dimensions in mm (w/d/h)	890/605/1300
Energy consumption in 365 days	2957 kWh
Heat output	1224 kJ/h
Climate rating	4 [1]
Refrigerant	R 290
Airborne acoustical noise emissions	47 dB(A)
Connection Rating	7.0 A
Voltage	230 V~
Cooling system	static
Defrosting	manual
Temperature range	-40 °C to -86 °C
Gradient *	k. A.
Max. fluctuation **	k. A.
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	stainless steel
Type of Control	electronic controller
Temperature display	external digital
Fault: warning signal	visual and audible
Interface	LAN (Ethernet)
volt-free alarm contact	yes
Adjustable Shelving	3
Shelf material	Edelstahl
Shelf loading	50 kg
Castors/type of castors	yes/swivel castors
Handle	Aluminium door handle compact
with integrated opening mechanism	yes
Lock	fitted
Door hinges	right
Insulation	103-180 mm
Defrost water drain	yes
Gross/net weight	330 / 288 kg
EAN-Nr.	9005382236772

Subject to modification. Timestamp: 09.10.2020

1 **Climate class** / Climate Rating: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C
3 +10°C to +25°C **4** +10°C to +30°C **5** +10°C to +40°C **7** +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

LIEBHERR