MFi REFRIGERATOR INCUBATOR

Select from our new series of Refrigerated Incubators. Our MFi 70 is a premium stainless steel refrigerator equipped with a Microprocessor Controller with timing function, that offers a total control over the temperature of your items. The features of this model make it unique and suitable to satisfy your high standard needs.

FEATURES

- Top Mounted System
- Cabinet Finish in Stainless Steel Interior/Exterior
- Automatic Defrost and Water Disposal
- 5 Adjustable Shelves per Door
- Available in Glass Door (TNG) or Solid Door (TN)
- Digital Display with Built-in Alarms
- Hi/Lo Readout



2°C to 40°C

700 L 1400 L

700w x 850d x 1990h 1400w x 850d x 1990h



NULINE

REFRIGERATION



MFi REFRIGERATOR INCUBATOR

	U		N	E.		
RE	REFRIGERATION					

Model	MFi70TN/G	MFi140TN/G	
Gross Capacity	700 L	1400 L	
External Dimensions in mm (w/d/h including castors)	700 x 850 x 1990	1400 x 850 x 1990	
Internal Dimensions in mm (w/d/h)	540 x 620 x 1320	1240 x 620 x 1320	
Packed Dimensions in mm (w/d/h including pallet)	750 x 880 x 2070	1450 x 880 x 2070	
Gross Weight - kg (packed weight)	134	225	
Net Weight - kg	120	201	
Voltage	240V		
Temperature Range	2°C to 40°C		
Ambient Temperature Range	10°C to 32°C		
Temperature Fluctuation	±1.5°C		
Refrigerant	R290		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Stainless Steel		
Inner Liner Material	Stainless Steel		
Door	Solid / Glass		
Door Hinge	RH	LH / RH	
Door Handle	Pull Handle		
Type of Controller	Digital / Microprocessor		
Temperature Display	External		
Data Logger	Optional		
Door Ajar Alarms	Optional		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Optional		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Optional		
Battery Back-up for Controller	Optional		
Power Requirement	10amp GPO		
Castors	Ye	es	
Adjustable Shelves	5	10	
Usable Shelf Area in mm(w/d)	530 x 652		
Light	LED		

