

UPSONIC

POWER

Cirrus



- High Output Power Factor Rating with Improved Efficiency
- Models Ranging from 1Kva to 10Kva with External Battery Packs available
- Virtualization Ready Software Solutions Hyper-V and VMware compatible
- Innovative Design with User Friendly LCD Screen
- Extensive Communication Options Available RS232 – Dry Contact – USB - SNMP

Upsonic Power Protection

To find out more contact
1800 634 307

Cloud based UPS Solutions

**POWER FOR THE
NON-STOP WORLD**

www.upsonic.com.au

**TRUE ONLINE
RACK/TOWER DESIGN**

Specifications - Cloud Series Rack/Tower

Model	Rackmount	CSCRT 1000	CSCRT 1000LR	CSCRT 2000	CSCRT 2000LR	CSCRT3000	CSCRT 3000LR	CSCRT 6000	CSCRT 10000	
Capacity	VA/W	1kVA/0.9kW	1kVA/0.9kW	2kVA/1.8kW	2kVA/1.8kW	3kVA/2.7kW	3kVA/2.7kW	6kVA/5.4kW	10kVA/9kW	
	Voltage	220/230/240VAC								
	Acceptable input	176-276VAC								
	Frequency	50/60Hz +/-5%"								
		45-55Hz								
	Phase	Single								
	Power Factor @ FL	≥ 0.99								
Output	Voltage	220/230/240VAC								
	Voltage Regulation	+/- 1%								
	Rated Power Factor	0.9								
	Waveform	True Sinewave								
	Frequency Stability	±0.1 Hz								
	Voltage Distortion	<5% IEC62040-3 Reference nonlinear load <2% Linear load"						<5%-IEC62040-3 Ref nonlinear load <2% Linear load"		
	Transfer time	0ms Normal Transfer among Line, Battery. 4ms Normal Transfer among Line, Bypass Mode. <10ms Exit HE mode for power Interruption						0ms - Normal Transfer among Line/Battery, Bypass Mode; 10ms Break-time- Force to Transfer to bypass with Mains2 out of tolerant or without phase lock ; <10ms-HE to battery transfer time.		
	Crest Factor	3:1								
	Efficiency AC-AC	88.24%	88.24%	89.55%	90%	92.47%	92.15%	>92%	>93%	
	Efficiency Eco Mode	>95%	>95%	>95%	>95%	>95%	>95%	>96%	>97%	
	Efficency DC-AC	83.13%	83.13%	84.76%	84.76%	88.47%	88.47%	>89%	>90%	
	Run time at 100% load	5 min		3 min		3 min				
	Run time at 50% load	15 min		10 min		10 min				
	DC start	YES	YES	YES	YES	YES	YES			
Battery	Type	12V 7Ah	N/A	12v 9Ah	N/A	12v 9Ah	N/A	12V 5Ah	12v 9Ah	
	Quantity	3		4		6		15	20	
	Voltage	36	36	48	48	72	72	180VDC	240VDC	
	Recharge time	<3hours to 90%		<3hours to 90%		<3hours to 90%				
	Charger capacity	1.5A	6A	1.5A	6A	1.5A	6A	>1A	>1.7A	
Display	LCD	YES								
Alarms	Audible and Visual	Audible and Programmable on/off								
	RS232	YES								
	Dry Contact	YES								
	USB	YES								
	SNMP	Optional								
Physical	Dimensions WHD	438 X 86.5 x 435	438 X 86.5 x 435	438X86.5x435	438 X 86.5 x 435	438 X 86.5 x 605	438 X 86.5 x 605	438 x 129 x 698	438 x 215.5 x 704	
	Weight	16.2	8.4	19.7	9.3	27.8	13	46kg	82.5kg	
	Outlets	8 x IEC	8 x IEC	8 x IEC	8 x IEC	8 x IEC 1 x 15A	8 x IEC 1 x 15A	4 x IEC 2 x 15A	8 x 15A	
Software	Winpower	CD supplied or Download from Web - Windows 95/98/XP/NT/2000								

Specifications - Cloud Series Tower

Model	Tower	CSCT 1000	CSCT 1000LR	CSCT 2000	CSCT 2000LR	CSCT3000	CSCT 3000LR
Capacity	VA/W	1kVA/0.8kW	1kVA/0.8kW	2kVA/1.6kW	2kVA/1.6kW	3kVA/2.4kW	3kVA/2.4kW
	Voltage			220/230/240VAC			
	Acceptable input			176-276VAC			
	Frequency			"50/60Hz +/-5%"			
				45-55Hz			
	Phase			Single			
	Power Factor @ FL			≥ 0.99			
Output	Voltage			220/230/240VAC			
	Voltage Regulation			+/- 1%			
	Rated Power Factor			0.8			
	Waveform			True Sinewave			
	Frequency Stability			±0.2 Hz			
	Voltage Distortion			<5% IEC62040-3 Reference nonlinear load <3% Linear load			
				<5% @ bat > 12V/pc IEC62040-3 Reference nonlinear load <3% @ bat > 12V/pc Linear load"			
	Transfer time			Line --Battery Oms M1 input interrupt			
	Crest Factor			3:1			
	Efficiency AC-AC	88.89%	88.89%	88.9%	88.4%	89.22%	88.89%
	Efficiency Eco Mode	95.14%	95%	96.35%	95%	96.9%	95%
	Efficency DC-AC	86.07%	86.37%	86.37%	86.37	87%	87%
	Run time at 100% load	5 min		9 min		5 min	
	Run time at 50% load	14 min		21 min		15 min	
	DC start			YES			
Battery	Type	12V 7Ah	N/A	12V 7Ah	N/A	12V 7Ah	N/A
	Quantity	3		8		8	
	Voltage	36	36	96	96	96	96
	Recharge time	5 hours to 90%		5 hours to 90%		5 hours to 90%	
	Charger capacity	1A	8A	1A	8A	1A	8A
Display	LCD			yes			
Alarms	Audible and Visual			Audible and Programmable on/off			
	RS232			Optional			
	Dry Contact			Optional			
	USB			YES			
	SNMP			Optional			
Physical	Dimensions WHD	145 x 400 x 220	145 x 400 x 220	192 x 460 x 347	192 x 460 x 347	192 x 460 x 347	192 x 460 x 347
	Weight	13	7	31	13	31	13
	Outlets	2 x Aus	2 x Aus	4 x Aus + 1 x IEC	4 x Aus + 1 x IEC	4 x Aus + 1 x IEC	4 x AUS + 1 x IEC
Software	Winpower	Download from Web - Windows 95/98/XP/NT/2000					

Specifications - Cirrus Series Reverse Views



Reverse CSCT 1000



Reverse CSCT 2000



Reverse CSCT 3000



Reverse CSCRT 1000 / 2000



Reverse CSCRT 3000



Reverse CSCRT 6000



Reverse CSCRT 10000

CIRRUS

Cloud based UPS Solutions from Upsonic

- High Output Power Factor Rating with Improved Efficiency
- Models Ranging from 1Kva to 10Kva with External Battery Packs available
- Virtualization Ready Software Solutions Hyper-V and VMware compatible
- Innovative Design with User Friendly LCD Screen
- Extensive Communication Options Available RS232 – Dry Contact – USB - SNMP

Operating System - Sistema Operativo

- Windows
- 95/98/ME/NT/2000/2003/2008/2012/SBS2011/XP/Vista/7/8
- Linux
- Linux AMD64
- Sun Solaris 7/8/9/10
- IBM Aix 4.3/5.1x/5.2x/5.3x
- HP-UX 11.x
- FreeBSD
- Unix Systems other than the operating systems mentioned
- MAC version - Versions per up to Mac 10.6
- Mac version - for Mac 10.7 and above

Upsonic Power Pty Ltd

ABN 51 070 890 390
 National Sales 1800 634 307
 National Fax 1800 634 308

Melbourne

9 Nicole Way
 Dandenong South, Vic 3175

Telephone: (03) 9706 0045
 Facsimile: (03) 9706 8003