

HYDRO LIFE®

WATER FILTRATION SYSTEMS

COMMERCIAL SERIES LINE

200
SERIES



250
Cartridge

200

200-E



230-C

230-E

Hydro Life 200 Series Filtration System

The 200 Series Filtration System removes or reduces rust, lead, dirt, chlorine, limescale, unpleasant taste and bad odor from your water. This system is ideal for slush equipment, water fountains, OCS equipment, coffee urns, and hot and cold cup vending equipment. Hydro Life uses Granulated Activated Carbon to control taste and odor, while patented KDF Media prevents bacteria growth and reduces limescale, saving your equipment from costly repairs. The Hydro Life 200 series water filter system and cartridge is easy to install, adapts to any incoming water line, and cartridge replacement is simple and reliable. The 200-E adapter kit provides easy in-field installation to retrofit Everpure® manifolds. (QL1, QL2, QL3, collar style head) The Hydro Life 230-C and 230-E systems feature the same high quality water filter as the other systems in the 200 series. The 230-C is a replacement cartridge that is compatible with Cuno® Filter systems. The 230-E replacement cartridge fits all existing Everpure® Filter systems. The 230-E Kit comes complete with manifold, gauge and cartridge that are compatible with Everpure Filter Systems. Also available is an Everpure adapter for those customers that already have original Everpure manifolds.

APPLICATIONS:

- Ice Machines
- Slush Equipment
- Water Fountains
- OCS Equipment
- Coffee Urns
- Hot & Cold Cup Vending Equipment

REDUCES OR CONTROLS:

- Chlorine
- Lead and other Heavy Metals
- Algae/Slime
- Organic Contaminants
- Taste/Odor
- Limescale
- Bacteria



For more information on the full line of Hydro Life filtration visit www.hydrolife.com or call 1-800-334-2004

HYDRO LIFE®

WATER FILTRATION SYSTEMS

COMMERCIAL SERIES LINE



SPECIFICATIONS:	200	200-E	230-C	230-E
Height:	13 ½"	13"	12 ¾"	13"
Width:	3 ¾"	3 ¾"	4"	4"
Depth:	4 ¼"	3 ¾"	4"	4"
Inlet/Outlet:	¾" FPT	Everpure® Adapter (will not fit SB heads)	Fits all existing Cuno® manifolds	Fits all existing Everpure® manifolds
*Capacity:	9,000 Gallons 34,069 Liters	9,000 Gallons 34,069 Liters	10,000 Gallons 37,854 Liters	15,000 Gallons 57,781 Liters
Flow Rate:	1.5 GPM 5.7 LPM	1.5 GPM 5.7 LPM	1.5 GPM 5.7 LPM	1.5 GPM 5.7 LPM
Working Pressure:	20-100 PSI non shock 1.38-6.89 Bar	20-100 PSI non shock 1.38-6.89 Bar	20-100 PSI non shock 1.38-6.89 Bar	20-100 PSI non shock 1.38-6.89 Bar
Maximum Operating Temp:	100° F / 38° C	100° F / 38° C	100° F / 38° C	100° F / 38° C
Quantity/Case:	6	6	6	6
Cartridge	250 included	250 included	—	—
Fitting included	✓	✓	—	—
Certification: TEI-NSF 42 & 53	✓	✓	Complies with NSF	Complies with NSF

*Dependent on water condition.
SB head: Low profile Everpure head



For more information on the full line of Hydro Life filtration visit www.hydrolife.com or call 1-800-334-2004