UFO LED HIGH BAY LIGHT User Manual

Product Features

- · NO UV or IR Radiation
- High Brightness SMD
- · High energy efficiency, low power consumption
- Long life-span,Low temperature rising

Packing List

1 × High Bay Light

1 × User Manual

Application

High bay is designed for

- FactoriesHighway toll stations
- Workshops
- Warehouses
- Supermarkets

- 1 × Hanging Ring
- Exhibition halls
- Stadiums
- Similar places

Precautions

Gas stations

- 1. Please cut off the power before installation. This product should be installed by a certified electrician in accordance with applicable national, state, and local building and electrical codes.
- Ensure all mounts are securely attached and will support the weight of the fixture. Failure to properly support the fixture may result in damage or injury, for which the manufacturer does not assume responsibility.

Specification

Item NO.	U920-100W U920-150W		U920-200W		
Power	100W	150W	200W		
LED Light Source	SMD2835*156pcs	SMD2835*280pcs	SMD2835*312pcs		
Color Temperature	5500K-6000K				
System Efficacy	150Lm/W				
LED lamp Life	50000h				
CRI	>80Ra				
IK Level	IK08				
IP Level	IP65				
Input Voltage	AC 100-277V				
Operating Temperature	-50 °F - 120 °F				
Product Size	φ255*130mm	φ265*140mm	φ300*140mm		
Material	Die cast aluminum + PMMA				

Features

- High-quality die-cast aluminum shell, strong corrosion resistance, not easy to rust, lightning protection, stainless steel screws, high-strength hard brackets.
- · High-transmittance optical lens, good light transmittance, uniform light, good uniformity of light effect.
- High lumen LED chip, high brightness, high color rendering, low light decay, smooth performance, soft and comfortable light.

POWER	LUMEN	Equivalent To	Equivalent To	Height Of Installat			
protection for short circuit/overcurrent/overvoltage/overheating.							

Wide-voltage anti-surge drive, fully enclosed aluminum alloy shell, plastic-filled package, full

POWER	LUMEN	Equivalent To Incandescent Light	Equivalent To Fluorescent Light	Height Of Installation
100W	15000Lm	800W FYI	200W FL	6-8m
150W	22500Lm	1200W FYI	300W FL	8-10m
200W	30000Lm	1600W FYI	400W FL	10-12m

WARNING

Only qualified personnel should install the lamp and ensure they follow the instruction manual. Any improper installation might cause falling, electric shock, fire, or other injury, damage or hazard.

Important Safety Information

- 1. To avoid damage, electric shock or fire, please do not modify the lamp without confirming with the supplier first.
- If the external flexible cable or cord of the lamp is damaged, it should only be replaced by the supplier, a service agent or qualified person.
- 3. Any improper installation might cause falling, electric shock, fire, or other injury, damage or hazard.
- 4. Please disconnect power before installation or any maintenance of the lamp.
- 5. Please disconnect power if it begins to smoke or emit odors, since fire or electric shock may occur.
- 6. Ask qualified electrician to inspect and maintain the light.
- 7. Please do not touch the power supply when the lamp is operating.
- 8. Avoid looking directly into the lamp when illuminated.
- 9. Pay attention to fire, electricity and shock.
- 10. Be aware that sulfides, corrosive and soluble chemicals can damage the lampshade and even cause the bulb to die.
- 11. The normal use environment temperature is -30° C ~ 50° C . Exceeding this range will adversely affect product life.

Warranty Limited

LIMITED **THREE-YEAR** WARRANTY. Should this product fail to perform satisfactorily due to a defect or poor workmanship within Three years from the date of purchase, return it to the place of purchase and it will be replaced, free of charge.

Incidental or consequential damages are excluded from the warranty.