

U920 Series



Features

- High-quality die-cast aluminum shell, strong corrosion resistance, not easy to rust, lightning protection, stainless steel screws, high-strength hard brackets.
- High-transmittance optical lens, good light transmittance, uniform light, good uniformity of light effect.
- High lumen LED chip, high brightness, high color rendering, low light decay, smooth performance, soft and comfortable light.
- Wide-voltage anti-surge drive, fully enclosed aluminum alloy shell, plastic-filled package, full protection for short circuit/overcurrent/overvoltage/overheating.

Optional Accessories



Wire Rope

Model	U920-100W	U920-150W	U920-200W
Watt Power	100W	150W	200W
LED Light Source	SMD2835*156pcs	SMD2835*280pcs	SMD2835*312pcs
Lighting Effect		150Lm/W	
Color Temperature		5500-6000K	
LED lamp life		50000H	
Colour Rendering Index		> 80	
Input Voltage		AC100-277V 50-60Hz	
Power factor		0.9	
IP Level		IP67	
IK Level		IK08	
Working temperature		-20°C -60°C	
Product size	Ø225*130mm	Ø265*140mm	Ø300*140mm
Qty		1pcs/ctn	
Carton size	250*245*130mm	290*295*140mm	330*325*140mm
GW.	1.8kg	2.3kg	2.9kg
Material	Die cast aluminum+PMMA		
Warranty	3 years		



Aluminum housing anti-corrosion



high transmisson optical lens