



Product: RSB20-0900VVM2TAABHH

Configurator: RSB20-0900VVM2TAABHH

Configurator Description

The RSB20 portfolio offers users a quality, hardened, reliable communications solution that provides an economically attractive entry into the segment of managed switches.

Technical Specifications

Product description

Description	Compact, managed Ethernet/Fast Ethernet Switch according to IEEE 802.3 for DIN Rail with Store-and-Forward-Switching and fanless design
Part Number	942014016
Port type and quantity	9 ports in total 1. uplink: 2 x 100BASE-FX, SM-SC 2. uplink: 100BASE-FX, MM-SC 6 x standard 10/100 BASE TX, RJ45

Product Life Cycle

Availability	passiv
Last Order Date	2023-12-31
Last Delivery Date	2024-06-30

More Interfaces

Power supply/signaling contact	1 x plug-in terminal block, 6-pin
V.24 interface	1 x RJ11 socket

Network size - length of cable

Twisted pair (TP)	0-100 m
Single mode fiber (SM) 9/125 µm	1. uplink: 0 - 32.5 km, 16 dB Link Budget at 1300 nm, A = 0.4 dB/km, 3 dB reserve, D = 3.5 ps/(nm x km)
Multimode fiber (MM) 50/125 µm	2. uplink: 0-5000 m, 8 dB Link Budget at 1300 nm, A=1 dB/km, 3 dB Reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm	; 2. uplink: 0 - 4000 m, 11 dB Link Budget at 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 500 MHz x km

Network size - cascadiability

Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time 0.3 sec.)

Power requirements

Operating Voltage	24V DC (18-32)V
-------------------	-----------------

Software

Switching	Fast aging, Static unicast/multicast address entries, QoS / Port prioritization (802.1D/p), TOS/DSCP prioritization, IGMP Snooping/Querier (v1/v2/v3)
Redundancy	HIPER-Ring (Manager), HIPER-Ring (Ring Switch), Media Redundancy Protocol (MRP) (IEC62439-2), RSTP 802.1D-2004 (IEC62439-1)
Management	TFTP, LLDP (802.1AB), V.24, HTTP, Traps, SNMP v1/v2/v3
Diagnostics	Signal contact, Device Status Indication, LEDs, RMON (1,2,3,9), Port Mirroring 1:1, System information, Self tests on cold start, SFP management (temperature, optical input and output power)
Configuration	Auto-Configuration Adapter ACA11 limited support (RS20/30/40,MS20/30), Automatic configuration undo (roll-back), Auto-Configuration Adapter ACA11 full support, BOOTP/DHCP client with auto configuration, HiDiscovery, DHCP Relay with Option 82, Command Line Interface (CLI), Full featured MIB support, WEB based management, Context sensitive help

Security	Local user management
Time synchronisation	SNTP Client, SNTP Server
Miscellaneous	Manual cable crossing
Presettings	Standard

Ambient conditions

Operating temperature	-40-+70
Storage/transport temperature	-40-+85 °C
Relative humidity (non-condensing)	10-95 %

Mechanical construction

Dimensions (WxHxD)	74 mm x 131 mm x 111 mm
Weight	410 g
Mounting	DIN rail
Protection class	IP20

Mechanical stability

IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 Conducted Immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)

EMC emitted immunity

EN 55032	EN 55032 Class A
----------	------------------

Approvals

Basis Standard	CE, FCC, EN61131
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2

Reliability

Guarantee	60 months (please refer to the terms of guarantee for detailed information)
-----------	---

Scope of delivery and accessories

Accessories	Rail Power Supply RPS 30, RPS 60, RPS90 or RPS 120, terminal cable, network management Industrial HiVision, auto-configuration adapter ACA11-RJ11 EEC, 19" installation frame
Scope of delivery	Device, terminal block, general safety instructions

© 2024 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.